

1

2

3

4

5

6

7

8

REFERENCE SPECIFICATIONS

-NFC 93425 (in compliance with HE 501)

PHYSICAL CHARACTERISTICS

-INSULATOR MATERIAL: THERMOPLASTIC UL94V0

-CONTACT MATERIAL: PHOSPHOR BRONZE

GOLD OVER NICKEL

-ACCESSORIES: BRASS ,cadmium plated yellow passivation

-SHELLS: STEEL ,cadmium plated yellow passivation

ELECTRICAL CHARACTERISTICS

-NOMINAL CURRENT: 7.5A

-CONTACT RESISTANCE: <= 7.3 m ohms

-CONTACT/CONTACT : >=1000 V

-CONTACT/GROUND : >=1200 V

-INSULATION RESISTANCE: >=5000 MOhms

ENVIRONMENTAL CHARACTERISTICS

- CLIMATIC CATEGORY: 55/125/56

TEMPERATURE RANGE -55°C TO +125°C

DAMP HEAT STEADY STATE 56 DAYS

SALT SPRAY 48 HOURS

MECHANICAL CHARACTERISTICS

- RETENTION AGAINST TORQUE: - Threaded insert: 0.7 N.m minimum

- Female screw : 0.5 N.m minimum

Series

DBML25S300

Shell size: E A B C D

see sheet 2

Front accessory definition

see sheet 2

Blank :without accessory

F :floating mounting

L :threaded insert M3

O :threaded insert UNC 4-40

V :female screw UNC 4-40

S :spacer

Contact number (see sheet 2)

9,15,25,37,50

Contacts

S :Socket

Termination type

3 :Straight version

Plating

00 : 500 matings/unmatings

43 : 500 matings/unmatings for harsh environment

25 WAY for Example

FCI

Copyright FCI.

Dr M PESSON

2006/11/06

Eng P LEGARE

2006/11/06

Chr P LEGARE

2006/11/06

Appr P LEGARE

2006/11/06

Product family

-

Spec.ref

-

surface

-

tolerance std

ISO 1302

ISO 406

ISO 1101

TOLERANCES UNLESS OTHERWISE SPECIFIED

0.X

±0.3

0.XX

±0.1

0.XXX

±0.05

projection

mm

size

A2

Scale

2:1

ECN

LS07-0273

FCI

title

SUB FEMALE DM HE501 series


with straight solder contact

catalog no

-

Customer

sheet 1 of 4



FRONT ACCESSORY	Blank without	F floating mounting	L insert M3 O insert UNC 4.40	V female screw UNC 4.40	S spacer
-----------------	---------------	---------------------	----------------------------------	-------------------------	----------

PART NUMBER	FRONT ACCESSORY
D*MxxS300	without
D*MFxxS300	floating mounting
D*MLxxS300	insert M3
D*MOxxS300	insert UNC 4.40
D*MVxxS300	female screw UNC 4.40
D*MSxxS300	spacer

PART NUMBER	FRONT ACCESSORY
D*MxxS343	without
D*MFxxS343	floating mounting
D*MLxxS343	insert M3
D*MOxxS343	insert UNC 4.40
D*MVxxS343	female screw UNC 4.40
D*MSxxS343	spacer

shell size	Contact number
#	XX
E	09
A	15
B	25
C	37
D	50

CROSS REFERENCES HE501 and FC1

HE501 P/N	FC1 P/N	FRONT ACCESSORY
HE501NxxYS4	D*MxxS300	without
HE501FxxYS4	D*MFxxS300	floating mounting

SCALE: 4

www.fciconnect.com		surface ISO 1302	tolerance std ISO 406 ISO 1101	projection size A2	mm Scale 2:1
		TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	M PESSON	2006/11/06	ANGULAR	0.X	±0.3
Eng	P LEGARE	2006/11/06	LINEAR	0.XX	±0.1
Chr	P LEGARE	2006/11/06	0° ±2°	0.XXX	±0.05
Appr	P LEGARE	2006/11/06	Product family	ECN LS07-0273	
				Spec ref	
FCI		SUB FEMALE DM HE501 series with straight solder contact		Rev. B	
catalog no				CUSTOMER	sheet 2 of 4

