one company > a world of innovation

Part Number: 0151310405

Status: **Active**

Overview: Pico-Lock Connector System
Description: Pico-Lock-to-Pico-Lock Off-the-Shelf (OTS) Cable Assembly, 1.00mm Pitch, Single Row, 450.00mm Length, 4 Circuits, Black

Documents:
Drawing (PDF)   Product Literature (PDF)
RoHS Certificate of Compliance (PDF)

Series image - Reference only

General
Product Family	Cable Assemblies
Series	15131
Application	Signal, Wire-to-Board
Assembly Configuration	Dual Ended Connectors
Connector to Connector	Pico-Lock-to-Pico-Lock
Overmolded	No
Overview	Pico-Lock Connector System
Product Literature Order No	987651-6143
Product Name	Pico-Lock
Type	Discrete Wire Assembly
UPC	191128284790

Physical
Cable Length	450.00mm
Circuits (Loaded)	4
Color - Resin	Black
Gender	Female-Female
Lock to Mating Part	Yes
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	3.044/g
Number of Rows	1
Pitch - Mating Interface	1.00mm
Single Ended	No
Termination Interface: Style	Crimp or Compression
Wire Insulation Diameter	0.60mm
Wire Size AWG	28
Wire/Cable Type	UL 1571

Electrical
Voltage - Maximum	150V

Material Info

Reference - Drawing Numbers
Sales Drawing	151310400-000

EU ELV
Not Relevant

EU RoHS   **China RoHS**
Compliant

REACH SVHC
Not Contained Per
-ED/88/2018 (15
January 2019)

Halogen-Free Status
Not Low-Halogen
For more information, please visit Contact US

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
15131 Series

Mates With
Pico-Lock Header 503763