LCR 083

General Purpose Filtered Power Entry Modules with Double Fuse Holder









Features

Compact double safety fuse modules, easy to use IEC inlet power entry filters with two safety fuses (on line and neutral). Available with QD tabs or solder terminals.


Typical Applications

Electronic equipment with safety and protection requirements.

Specifications

Rated Voltage Max. (V)	250 VAC Max.						
Rated Current (A)	1-10 A @ 40°C						
Operating Frequency (Hz)	50/60 Hz						
Hipot Rating							
Line to Line	1450 VDC						
Line to Ground	2250 VDC						
Case	Plated Steel						
Packaging Quantity	126 Pcs per Carton						

Electrical Schematic



Leakage Current	
@ 250 VAC 50 Hz	0.42 mA Max.
@ 115 VAC 60 Hz	0.23 mA Max.
Climatic Category (EN60068-1)	25/85/21
IP Class	IP51

Model No.	Rated Current	Unit Weight (g)	Terminal Options				
	(A) @ 40°C		In	Out			
083.00101.00	1	62	IEC Inlet Socket	QD 6.35*0.8			
083.00301.00	3	64	IEC Inlet Socket	QD 6.35*0.8			
083.00601.00	6	64	IEC Inlet Socket	QD 6.35*0.8			
083.01001.00	10	66	IEC Inlet Socket	OD 6.35*0.8			




LCR 083


General Purpose Filtered Power Entry Modules with Double Fuse Holder





LCR 083 Mechanical Outlines





LCR 083 Mechanical Dimensions (mm)

Model No.	А	В	С	D			G	Н		R	S	Т	U	
083.00101.00	50.9	28.5	34	36.1	66	44.5	2*Ф4.0	8.8	12	3	29.5	33.5	36.1	2.1
083.00301.00	50.9	28.5	34	36.1	66	44.5	2*Ф4.0	8.8	12	3	29.5	33.5	36.1	2.1
083.00601.00	50.9	28.5	34	36.1	66	44.5	2*Ф4.0	8.8	12	3	29.5	33.5	36.1	2.1
083.01001.00	50.9	28.5	34	36.1	66	44.5	2*Ф4.0	8.8	12	3	29.5	33.5	36.1	2.1

LCR 083 Insertion Loss in dB Measured in a 50 Ω System

