



注 1. 使用時の適用回転トルクの値 12kg-cm 最大

(-1: 類似 NO. 202644-3)

PART NO		"A"	"B"	MATERIAL&FINISH	NAME	ITEM			
7-3	7-2	7-1	-3	9	-				
1	-	-	-	-	1.8	7.2	BRASS, Ni PLATED	JACK-SCREW BODY	③
-	1	-	-	-	2.6	26.0	BRASS, Ni PLATED	JACK-SCREW BODY	③
-	-	1	-	-	3.65	7.2	BRASS, Ni PLATED	JACK-SCREW BODY	③
-	-	-	1	-	1.8	7.2	BRASS, TIN PLATED	JACK-SCREW BODY	③
-	-	-	-	-	2.6	26.0	BRASS, TIN PLATED	JACK-SCREW BODY	③
-	-	-	-	1	3.65	7.2	BRASS, TIN PLATED	JACK-SCREW BODY	③
1	1	1	1	1	-	-	STAINLESS STEEL ORGANIC COATING	JACK-SCREW PIN	②
1	1	1	1	1	-	-	STAINLESS STEEL ORGANIC COATING	JACK-SCREW TIP	①
QTY		"A"	"B"	MATERIAL&FINISH		NAME		ITEM	

G	REVISED PER ECR-17-004338	C.L	N.Y	20APR17
F	REVISED	T.N	N.Y	16APR 2013
E	ADDED-3 ECR J82-6768	H.D	H.D	19/5/82
D	ADDED-2 (P-DWG)	J.A	J.D	16/7/82
C	ECR J6-3956	J.A	J.D	16/10/76
B	ADDED NOTE 1	H.S	J.D	24/1/82
B1	202644-3 WAS 202644-2	J.A	J.D	20/1/82
A	REVISED (REV. 0)	J.A	J.D	20/1/82
A	REVISED (REV. 0)	J.R	J.D	20/1/82
O1	REVISED (REV. 0)	J.R	J.D	19/3/82
H	REVISED PER ECR-18-009061	E.S	N.Y	14JUN18
LTR.	変更 (REVISION RECORD)	DR.	CHK.	DATE

COPYRIGHT 2012 BY Tyco Electronics Japan G.K.

参考図面 (CUSTOMER COPY) (REFERENCE ONLY)

TE Connectivity

材料 (MATERIAL) 上参照

仕上 (FINISH) 上参照

DR. M. Kobayashi 7/9/79

CHK. M. Iwatake 9/30/79

DE. M. Iwatake 9/30/79

APP. M. Iwatake 9/30/79

結合部品 (REQUIRED PER ASSEMBLY)

記事 (DESCRIPTION)

一般公差 (TOLERANCE) ±0.4 EXCEPT AS NOTED ±1.0

尺度 (SCALE) 2-1

分類 (CLASS) 型式 (TYPE)

LOC SIZE 番号 (NO) REV. JB C-170995 H

名称 (NAME) 可動ジャックスクリュー (H)

単位: 寸 単位: 尺 DO NOT SCALE PRINT