


LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-		B	REVISE PER ECO-11-019143	21/SEP/11	ECC	PJB

△ MATERIALS AND FINISH:

- HOUSING: PC, COLOR: BLACK
- SEAL: SILICONE RUBBER, COLOR: BLUE
- CONTACTS: COPPER ALLOY
- FINISH: TIN IN CONTACT AREA OVER NICKEL UNDERPLATE
- WIRE: 22 AWG, STRANDED, UL 1007 STYLE


2. MUST COMPLY WITH DIRECTIVE 2002/95/EC (ROHS)

3 REFERENCE CHART FOR SPECIFIC WIRE COLOR/POSITION



	WIRE COLOR 	WIRE COLOR 
2	BLACK	BLACK
1	RED	RED
POSN	- 1	- 2

525.0 +/- 5.0	2	2106841-2
209.0 +/- 4.0	2	2106841-1
LENGTH	POSN	TE P/N

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 290CT2009 WM VAN SCYOC CHK 290CT2009 M MOSTOLLER		 TE Connectivity	
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±. 1 PLC ±0.2 2 PLC ±. 3 PLC ±. 4 PLC ±. ANGLES ±. FINISH		NAME CABLE ASSEMBLY, PLUG, SLIMSEAL SSL CONNECTOR	
		PRODUCT SPEC 108-2391		RESTRICTED TO	
MATERIAL		APPLICATION SPEC 114-13261		SIZE CAGE CODE DRAWING NO A200779 C-2106841	
WEIGHT		CUSTOMER DRAWING		SCALE 4:1 SHEET OF 1 REV B	