

RACON 12 - Tactile switch solder terminals for PCB, outward

1.14.001.506/0000

For keycaps, refer to RK 90:



Dimensions	
Length of housing	12 mm
Width of housing	12 mm
Overall height	4,95 ^{±0,1} mm
Mechanical design	
Mounting	soldering
Terminals	THT outward
Contact system	snap-action contact
Contact arrangement	1 NO
Contact materials	Au
Illumination	no
Mechanical characteristics	
Operating force	3.5 N
Switching travel	0.61 ^{±0,1} mm
Electrical characteristics	
Rated voltage min.	0.02 V
Rated voltage max.	35 V
Rated current min.	0.01 mA
Rated current max.	100 mA
Rated power max. (ohmic load)	1 W
Contact resistance when new max.	100 mΩ
Insulation resistance	10 ⁹ Ω
Other specifications	
Ambient temp. operating min.	-40 °C
Ambient temp. operating max.	+90 °C
Resistance to environment	DIN EN 60068-2 -14,-30,-33 and -78
Operating life	1,000,000 cycle
Solderability / Solder heat resistance	DIN EN 60068-2-20
Flammability of materials	UL 94 HB
Packing	tubes à 45 pieces
Produkt code	F1
ROHS compliant	yes
REACH compliant	yes

PCB footprint, view on component side



