



### Main

Range	Linergy
Product name	HK
Product or component type	Mounting plate
Poles description	3P
[Ith] conventional free air thermal current	25 A
I <sup>2</sup> t on activation	200000 A <sup>2</sup> .s
Number of cables	3 cable(s) 0.01 in <sup>2</sup> (4 mm <sup>2</sup> ) at 221 °F (105 °C)
Width	2.13 in (54 mm)
Height	7.48 in (190 mm)
Depth	2.4 in (61 mm)

### Complementary

[U <sub>i</sub> ] rated insulation voltage	690 V conforming to IEC 60439-1
9 mm pitches	6
Product weight	0.51 lb(US) (0.23 kg)

### Environment

standards	IEC 60439
product certifications	CSA DNV LR0S (Lloyds register of shipping) UL

### Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>	For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>

### Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.