

## Printed-circuit board connector - SPC 5/ 2-STCL-7,62 AG - 1702695

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB connector, nominal current: 41 A, number of positions: 2, pitch: 7.62 mm, connection method: Push-in spring connection, color: green, contact surface: Tin



### Key Commercial Data

|              |                                                                                    |
|--------------|------------------------------------------------------------------------------------|
| Packing unit | 50 pc                                                                              |
| GTIN         |  |
| GTIN         | 4046356624275                                                                      |

### Technical data

#### Dimensions

|             |         |
|-------------|---------|
| Pitch       | 7.62 mm |
| Dimension a | 7.62 mm |

#### General

|                                  |                           |
|----------------------------------|---------------------------|
| Range of articles                | SPC 5/...-STCL            |
| Number of positions              | 2                         |
| Connection method                | Push-in spring connection |
| Rated voltage (III/3)            | 1000 V                    |
| Connection in acc. with standard | EN-VDE                    |
| Nominal current $I_N$            | 41 A                      |
| Nominal cross section            | 6 mm²                     |

#### Connection data

|                                                                            |          |
|----------------------------------------------------------------------------|----------|
| Conductor cross section solid min.                                         | 0.2 mm²  |
| Conductor cross section solid max.                                         | 10 mm²   |
| Conductor cross section flexible min.                                      | 0.2 mm²  |
| Conductor cross section flexible max.                                      | 6 mm²    |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.25 mm² |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 6 mm²    |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.25 mm² |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 4 mm²    |
| Conductor cross section AWG min.                                           | 24       |
| Conductor cross section AWG max.                                           | 8        |

# Printed-circuit board connector - SPC 5/ 2-STCL-7,62 AG - 1702695

## Technical data

### Connection data

|                                                                                         |          |
|-----------------------------------------------------------------------------------------|----------|
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.25 mm² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1.5 mm²  |


### Standards and Regulations

|                                  |        |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|----------------------------------|--------|

### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

## Drawings



Click and Lock system method of operation

## Approvals

### Approvals

## Printed-circuit board connector - SPC 5/ 2-STCL-7,62 AG - 1702695

### Approvals

Approvals

EAC

---

Ex Approvals

---

### Approval details

|     |                                                                                   |         |
|-----|-----------------------------------------------------------------------------------|---------|
| EAC |  | B.01742 |
|-----|-----------------------------------------------------------------------------------|---------|

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>