

HLW TIES ARE CUSTOM PRINTED,
SEE DIMENSIONS G & H FOR MAXIMUM PRINTING AREA.

HLWM TIES ARE MARKER TIES WITH A WRITE-ON AREA
(SEE DIMENSIONS G & H)

LOOP: NYLON

HOOK: NYLON

A REF.

C REF.

Dimensions: A, B, C, D, E, F, G, H.

PANDUIT PART NO.	BUNDLE DIA.		A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	F in (mm)	G in (mm)	H in (mm)	MIN. LOOP TENSILE lbs.(N)	CROSS SECTION	APPROXIMATE WEIGHT lbs/100 PARTS (g)
	MIN. in (mm)	MAX. in (mm)											
HLW1.5S*	.25 (6.4)	1.5 (38.1)	.076 (1.9)	.79 (20.1)	.080 (2.0)	3.2 (81)	3.2 (81)	6.0 (152)	.5 (12.7)	2.5 (63.5)	50 (222)	STANDARD	.24 (108)
HLW3S*		3.2 (81.3)				6.2 (157)	6.2 (157)	12.0 (305)		3.1 (78.7)			.48 (217)
HLWM1.5S		1.5 (38.1)				3.2 (81)	3.2 (81)	6.0 (152)		2.5 (63.5)			.24 (108)
HLWM3S		3.2 (81.3)				6.2 (157)	6.2 (157)	12.0 (305)					.48 (217)

1) SEE www.panduit.com FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE AND COLOR.
2) MINIMUM 2" OVERLAP REQUIRED TO ACHIEVE LOOP TENSILE RATING.

W10001CQ/01.PRT

PANDUIT CORP. TINLEY PARK, ILLINOIS

HOOK & LOOP TIES

HLW SERIES ARE CUSTOM PRINTED
HLWM SERIES ARE MARKER TIES

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ± .25 (.XXX) ± .030
(.XX) ± .125 ANGLES ±

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

DRAWN BY
JABO

MAT'L:

SCALE	NONE
-------	------

DATE	7/21/09
------	---------

WOVEN NYLON
HOOK/LOOP

DRAWING NO.

SS - 27598

DWG
A
SIZE

--	----	---		CHANGED NOTE 1 SEE CURRENT PRICE SHEET... TO SEE www.panduit.com ...	---	--				
--	----	---		CORRECT BUNDLE DIA PER RAM1/DWW	---	--				
01	8/27/08	JABO		MOVED DIMS G & H TO DIMENSION AREA	27598	01				
REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP		