XZCC8FDM40V



Main

Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Straight female connector M8, 4 pins
Collar material	Metal
Status LED	Without
Cable connection	Vampire clip / wire size <= 0.25 mm ² / clamping capacity <= 0.2 in (5 mm)

Complementary

Cable gland type	M9.5	
Cable connector fixing	Screw-on	
System Voltage	60 V AC 75 V DC	
Line Rated Current	4 A	
Enclosure material	Plastic	
Insulating resistance	>1 GΩ	
Contact resistance	<= 10000 μOhm	
Product weight	0.02 lb(US) (0.01 kg)	

Environment

IP degree of protection	IP67
ambient air temperature for operation	-13158 °F (-2570 °C)


Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0726 - Schneider Electric declaration of conformity	Compliant - since 0726 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty Warranty period

Warranty period	18 months
-----------------	-----------

Dimensions



Connections and Schemes

