







REV.	DATE	DESCRIPTION
NC	05/17/99	INITIAL RELEASE
A	04/06/06	UPDATE DRAWING FORMAT
B	02/05/07	MODIFY NOTES



RECOMMENDED
MOUNTING HOLE



NOTE:

1. MAX. PANEL THICKNESS = 2.5mm
2. CONTACT PLATING: GOLD PL. 50MIN THICK
OVER NICKEL PL. 100MIN THICK OVER COPPER STRIKE.

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020" DO NOT SCALE DRAWING	APPROVALS	DATE	Amphenol Connex					
8						DRAWN	G.R.S.						02/05/07
7						CHECKED							
6						ISSUED			PART DESCRIPTION BNC BULKHEAD ISOLATED RECEPT. JACK 50ohm				
5	HEX NUT	BRASS	NICKEL	1		SHEET	1 OF 1						
4	LOCK WASHER	BRASS	NICKEL	1					PART NO. 112624				
3	CONTACT PIN	PHOS. BRONZE	SEE NOTE 2	1									
2	INSULATOR	TEFLON	NATURAL	1					DWG. NO. 112624.DWG				
1	BODY	BRASS	NICKEL	1									
	DESCRIPTION	MATERIAL	FINISH	QTY	CAD FILE C:/112/112624.DWG			REV. B	SIZE A	SCALE NA			