

LCA Series

Subminiature Snap-acting Switches



Features/Benefits

- Compact design
- Long life and high electrical capacity
- Quick connect, solder terminals, PC terminals
- Wide variety of actuator styles
- RoHS compatible

Typical Applications

- Motorized equipment
- Sump pump
- Thermostatic controls

UL61058-1



Specifications

CONTACT RATING: From low level to 10.1 AMPS @ 125/250 V AC

ELECTRICAL LIFE: see chart below

MECHANICAL LIFE: 300,000 cycles.

INSULATION RESISTANCE: 100 M ohm min.

DIELECTRIC STRENGTH: 1,500 Vrms min. @ sea level.

OPERATING TEMPERATURE: -40°C to +125°C

OPERATING FORCE: 150 grams at actuator button MAX.

Forces are less at free end of lever actuators; (see ACTUATOR'S option sections).

MOUNTING: 2-56 screws, torque 2.3 in/lbs max.

Materials

SWITCH HOUSING: Thermoplastic polyester

ACTUATOR BUTTON: Thermoplastic polyester.

SPRING: Copper alloy.

PIVOT: Copper alloy.

MOVABLE CONTACTS: Silver alloy

STATIONARY CONTACTS: Silver alloy

TERMINALS: Copper alloy.

ACTUATOR LEVER: Stainless steel.

NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service center.

Build-A-Switch

To order, simply select desired option from each category and place in the appropriate box. Available options are shown and described on pages J-36 thru J-39. For additional options not shown in catalog, consult Customer Service Center.

Series **LCA** SP, Mom.

Electrical Rating

Operating Force **150** 150 grams

Option Code	UL 1054	UL 61058-1	E4
01	0.1 A 125/250 V AC 1E6	0.1 A 125/250 V AC 1E6	0.1 A 125/250 V AC 1E6
06	6 A 125/250 V AC 1E4	6 A 125/250 V AC 1E4	6 (2)A 125/250 V AC 1E4
10	10.1 A 125/250 V AC 1E4	10.1 A 125/250 V AC 1E4	10.1 A 125/250 V AC 1E4
S5	NA	5 A 125/250 V AC 1E5	NA

Actuator

- P00** Pin plunger
- T05** 4.8 mm short lever
- T06** 6.8 mm lever
- T09** 8.8 mm lever
- T12** 12.9 mm lever
- T16** 15.2 mm lever
- T18** 18.1 mm lever
- T21** 20.1 mm lever
- T23** 23.4 mm lever
- T43** 43.5 mm lever
- S06** 6.0 mm simulated lever
- S09** 9.2 mm simulated lever
- A05** 5.0 mm lever roller

Terminations

- S** Solder
- Q** .110 Quick Connect
- P** PC Thru Hole
- L** Left Form PC
- R** Right Form PC

Circuitry

- C** SPDT
- W** SPST N.C.
- Y** SPST N.O.



Third Angle
Projection

Dimensions are shown: mm

Specifications and dimensions subject to change



SERIES

Technical drawing of a mechanical part, showing two views: a front view (left) and a side view (right).

Front View Dimensions:

- Overall width: 19.8
- Overall height: 9.5
- Top horizontal distance from left edge to first vertical feature: 7.5
- Top horizontal distance between vertical features: 2.1
- Left vertical distance from top edge to first horizontal feature: 2.45
- Left vertical distance between horizontal features: 2.4
- Left vertical distance from bottom edge to first horizontal feature: 7.05
- Horizontal distance from left edge to first vertical feature: 1.86
- Horizontal distance between vertical features: 8.8
- Horizontal distance from second vertical feature to right edge: 7.3
- Horizontal distance from left edge to second vertical feature: 5.1
- Horizontal distance between vertical features: 9.5
- Horizontal distance from second vertical feature to right edge: 0.6
- Horizontal distance from left edge to first vertical feature: $\phi 2.5$
- Horizontal distance from second vertical feature to right edge: $\phi 2.4$

Side View Dimensions:


- Overall width: 6.4
- Overall height: 10.6
- Top horizontal distance from left edge to first vertical feature: 3.4
- Left vertical distance from top edge to first horizontal feature: 1.0
- Left vertical distance between horizontal features: 1.2
- Left vertical distance from bottom edge to first horizontal feature: 3.3
- Horizontal distance from left edge to first vertical feature: 1.0
- Horizontal distance between vertical features: 3.3
- Horizontal distance from second vertical feature to right edge: 1.2
- Horizontal distance from left edge to second vertical feature: 3.3
- Horizontal distance between vertical features: 3.3
- Horizontal distance from second vertical feature to right edge: 1.2
- Horizontal distance from left edge to second vertical feature: 3.3
- Horizontal distance between vertical features: 3.3
- Horizontal distance from second vertical feature to right edge: 1.2
- Horizontal distance from left edge to first vertical feature: $R0.3$
- Horizontal distance from second vertical feature to right edge: $R0.3$

ELECTRICAL RATING

* Note: See Technical Data section of this catalog for RoHS compliant and compatible definition and specifications.

OPERATING FORCE

OPTION CODE	OPERATING FORCES (grams)
150	150 grams max.



Snap-acting



LCA Series

Subminiature Snap-acting Switches

ACTUATOR 



A05 LEVER ROLLER

SXX SIMULATED ROLLER



TXX LEVER

P00



ACTUATOR OPTION CODE	A mm	B ref. mm	C mm	D mm	E mm	Diff. Motion mm	Oper. Force max. grams	Release Force min. grams	Over Travel min.
	LENGTH OF LEVER	Lever length for front mtg. hole to OP	PRE TRAVEL (MAX)	OPERATING POSITION	FREE POSITION (MAX)	max			
P00	NA	NA	1.10	8.55 ± 0.3	9.35	0.20	150	25	0.4
T05	16.70	4.80	3.60	8.95 ± 0.8	11.75	0.80	50	6	0.6
T06	18.70	6.80	4.03	8.9 ± 0.9	12.09	0.90	45	5	0.67
T09	20.60	9.10	5.64	9.15 ± 1.35	13.45	1.83	33	2	0.75
T12	24.80	12.90	3.35	8.95 ± 1.5	13.10	1.19	34	2	0.89
T16	27.10	15.20	7.20	9.15 ± 1.7	15.15	1.30	40	1	0.70
T18	30.00	18.10	7.70	8.95 ± 1.9	14.65	1.50	32	1	1.2
T21	32.00	20.10	8.00	8.15 ± 1.85	15.55	1.60	35	1	1.0
T23	35.20	23.40	8.60	8.95 ± 2.0	15.55	1.80	25	1	1.5
T43	55.20	43.50	10.45	8.95 ± 3.0	19.25	2.90	15	1	1.0
S06	17.90	6.00	3.86	10.85 ± 0.9	17.81	0.86	47	5	0.64
S09	21.10	9.20	5.7	16.15 ± 1.5	20.35	1.00	42	2	1.0
A05	16.60	5.00	3.8	14.65 ± 0.8	17.65	0.80	50	6	0.6







Dimensions are shown: mm
Specifications and dimensions subject to change

LCA Series Subminiature Snap-acting Switches

TERMINATIONS





S SOLDER

Q QUICK CONNECT






P PC THRU HOLE

L LEFT FORM PC



R RIGHT FORM PC




Snap-acting

CIRCUITRY

C SPDT (Single Pole, Double Throw)

W SPST N.C. (Single Pole, Single Throw, Normally Closed)

Y SPST N.O. (Single Pole, Single Throw, Normally Open)



Third Angle
Projection

Dimensions are shown: mm
Specifications and dimensions subject to change

C&K

12 Jun 20

J-43

www.ckswitches.com