



SPECIFICATIONS											
WIRING	INPUT		OUTPUT				SHAFT ROTATION TO INCREASE VOLTAGE	TERMINAL CONNECTIONS			
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD		CONSTANT IMPEDANCE LOAD		FOR INCREASING VOLTAGE AS VIEWED FROM BASE END			
				MAX. AMPS	MAX. KVA	MAX. AMPS		MAX. KVA	INPUT	JUMPER	OUTPUT
SINGLE PHASE	240	60	0-240	5.0	1.20	7.0	1.68	CW	1-4	---	4-3
								CCW	1-4	---	1-3
UNLESS OTHERWISE SPECIFIED, TOLERANCE IS ±							TITLE: SPEC. CONTROL DRAWING				
DECIMALS .03							HOLES .002				
ANGLES 1°							DRAFT 1-1/2°				
MATERIAL:							UNITS IN [mm]				
ALL DIMENSIONS APPLY AFTER PLATING							CAGE CODE 83008				
DRAWN BY S.A. SMITH							DATE 9/25/97				
CHECKER							DATE				
ENGINEER							DATE				
WEIGHT APPROX. 9 LBS							DO NOT SCALE DWG.				
SCALE 1=1							SHEET 1 OF 1				
DWG. NO. 031-3260							D				

