



SPECIFICATIONS											
WIRING	INPUT		OUTPUT				SHAFT ROTATION TO INCREASE VOLTAGE	TERMINAL CONNECTIONS			
	VOLTS	HERTZ	VOLTS	CONSTANT CURRENT LOAD		CONSTANT IMPEDANCE LOAD		FOR INCREASING VOLTAGE AS VIEWED FROM BASE END			
				MAX. AMPS	MAX. KVA	MAX. AMPS		MAX. KVA	INPUT	JUMPER	OUTPUT
SINGLE PHASE	240	60	0-240	5.0	1.20	7.0	1.68	CW	1-4	---	4-3
								CCW	1-4	---	1-3
UNLESS OTHERWISE SPECIFIED, TOLERANCE IS ±			UNITS			TITLE: SPEC. CONTROL DRAWING					
DECIMALS			IN [mm]			SPEC. CONTROL DRAWING					
.XX			.002			MODEL: 1220B					
.XXX			1°			DRAWN BY S.A. SMITH					
.005			1-1/2°			DATE 9/25/97					
MATERIAL:			ALL DIMENSIONS APPLY AFTER PLATING			FIRST USED ON					
						DO NOT SCALE DWG.					
						CAGE CODE 83008					
						WEIGHT APPROX. 9 LBS					
						SCALE 1=1					
						SHEET 1 OF 1					
						DWG. NO. 031-3260					

