







REV.	DATE	ECR NO.	DESCRIPTION
NC	05/07/00	XXXXXX	INITIAL RELEASE
A	10/18/06	XXXXXX	UPDATE DRAWING FORMAT
B	08/31/11	2221	CHANGE THE CONTACT'S PLATING AND ADD THE ELECTRICAL SPECS.



1. IMPEDANCE: 50 OHM
2. FREQUENCY RANGE: DC - 11 GHz
3. DIELECTRIC WITHSTANDING VOLTAGE: 2500 VRMS MIN.
4. DURABILITY: 500 CYCLES MIN.
5. CRIMPED FERRULE
HEX CRIMP SIZE .610"
6. CONTACT PIN TO SOLDER
7. MAX. PANEL THICKNESS=6.5mm

7	FERRULE	BRASS	NEXCOTE	1
6	CONTACT PIN	PHOSPHOR BRONZE	GOLD	1
5	HEX NUT	BRASS	NEXCOTE	1
4	LOCK WASHER	BRASS	NEXCOTE	1
3	GASKET	SILICON RUBBER	RED	1
2	INSULATOR	PTFE	NATURAL	1
1	BODY	BRASS	NEXCOTE	1
	DESCRIPTION	MATERIAL	FINISH	QTY

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE:
0.5 - 8mm ± 0.20mm
8 - 30mm ± 0.40mm
30 - 120mm ± 0.50mm

UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE:
.020 - .315 = ± 0.007"
.315 - 1.180 = ± 0.015"
1.180 - 4.724 = ± 0.020"

DO NOT SCALE DRAWING

APPROVALS	DATE
DRAWN M.ZHANG	08/31/11
CHECKED	
ISSUED	
SHEET 1 OF 1	
CAD FILE	C:/CONNEX/172264.DWG

Amphenol Connex			
PART DESCRIPTION			
N BULKHEAD CRIMP JACK (FOR LMR 600 CABLE)			
PART NO.			
172264			
DWG. NO.	172264.DWG	REV.	B
SIZE	A	SCALE	NA