



### Main

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessories
Product specific application	Heavy hoisting applications Light hoisting applications Medium hoisting applications
Product compatibility	XKB XKD XKM
Accessory / separate part type	Potentiometer
Condition of use	For standard applications
Ohmic value	10000 Ohm
Size	15 mm

### Complementary

Standards	UTE 93-265
Potentiometer characteristic	Continuous rotational operation Linear function
Operating angle	360 °
Mechanical durability	3000000 cycles
Centre tap	Wired out to terminal
Centre tap dead zone	2 ° +/- 1 %
Power dissipation in W	3 W 85 °C
Connections - terminals	Flying leads from soldered standard tags
Product weight	0.13 lb(US) (0.06 kg)

### Environment

mounting mode	By the body
---------------	-------------

### Contractual warranty

Warranty period	18 months
-----------------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.