

RAFIX 16 - Selector switch, square collar, alignable without gaps, illuminated, momentary
1.30.073.691/2000



Only use contact blocks with momentary function.

General information

| | |
|-------------------|-------------------|
| Actuator | handle |
| Marking of handle | translucent white |
| Form of collar | square alignable |

Dimensions

| | |
|-------------------|------------------|
| Collar dimensions | 24.95 x 24.95 mm |
| Collar dimensions | 24.95 x 24.95 mm |
| Overall height | 17.1 mm |
| Mounting depth | 44.7 mm |
| Mounting hole | 16.2 mm |
| Key grid | 25 x 25 mm |

Mechanical design

| | |
|---------------------|----------------------------|
| Mounting | ring nut |
| Contact function | momentary |
| Contact arrangement | according to contact block |
| Illumination | yes |
| Rotating angle | 2 x 40° |

Mechanical characteristics

| | |
|-------------|--------|
| Torque max. | 1.3 Nm |
|-------------|--------|

Other specifications

| | |
|-------------------------------------------------|------------------------------------------|
| Operating life (operations) | 30,000 cycle |
| Degree of protection from front side | IP65 (DIN EN 60529) |
| Operation temperature min. | -25 °C |
| Ambient temp. operating max. without lamp / LED | +70 °C |
| Ambient temp. operating max. with lamp /LED | +55 °C |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +85 °C |
| Environmental resistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| ROHS compliant | yes |
| REACH compliant | yes |

Panel cut-out

