

PCB terminal block - ZFKKDSA 1,5C-5,0-6 GY - 1708504

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)




PCB terminal block, nom. voltage: 400 V, pitch: 5 mm, number of positions: 6, color: gray

The figure shows a 15-position version

Your advantages

- ☑ Defined contact force ensures that contact remains stable over the long term
- ☑ Clamping space opened by means of fixed screwdriver enables convenient conductor connection
- The latching on the side enables various numbers of positions to be combined



Key Commercial Data

Packing unit	50 pc
GTIN	4 055626 123455
GTIN	4055626123455

Technical data

Dimensions

Pitch	5 mm
Solder pin [P]	3.7 mm
Hole diameter	1.1 mm

General

Range of articles	ZFKKDS(A) 1,5C
Insulating material group	I
Nominal cross section	1.5 mm²
Flammability rating according to UL 94	V0
Number of positions	6

Standards and Regulations



PCB terminal block - ZFKKDSA 1,5C-5,0- 6 GY - 1708504

Technical data

Flammability rating according to UL 94	V0
Environmental Product Compliance	
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values
Approvals	
Approvals	
Approvals	
EAC	
Ex Approvals	
Approval details	
EAC ER	B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com