Product data sheet Characteristics

9001KP36LWW9

round pilot light Ø 30 - white - LED BA 9s - 48V AC/DC- IP66



Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Range of product	Harmony 9001K
Product or component type	Pilot light
Device short name	9001K

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Shape of signaling unit head	Round	
Lens type	Domed plastic	
Cap/operator or lens colour	White	
Light source	White LED	
Bulb base	BA 9s	
Light block supply	Direct 48 V AC/DC	
Connections - terminals	Screw clamp terminals, 1 x 0.222 x 1.5 mm² IEC 60947-1	
Tightening torque	7.08 lbf.in (0.8 N.m) IEC 60947-1	
Shape of screw head	Cross slotted	
Shape of screw head	Cross slotted	
Operating position	Any position	
[Ui] rated insulation voltage	250 V 2)IEC 60947-1	
[Uimp] rated impulse withstand voltage	2.5 kV IEC 60947-1	
Short-circuit protection	10 A cartridge fuse IEC 60947-5-1	
Light source	High luminosity LED	
[Ith] conventional free air thermal current	10 A	
CAD overall width	2.13 in (54 mm)	
CAD overall height	2.76 in (70 mm)	
CAD overall depth	1.65 in (42 mm)	
[Us] rated supply voltage	48 V AC/DC	
Net weight	0.30 lb(US) (0.134 kg)	
Device presentation	Complete product	

Environment

Standards	CSA C22.2 No 14 EN/IEC 60947-5-4 EN/IEC 60947-1 UL 508 EN/IEC 60947-5-1 JIS C 4520 JIS C 852
Product certifications	UL 508 NEMA
Protective treatment	TC
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27
Overvoltage category	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6

Ordering and shipping details

0 11 0		
Category	21429 - 9001 SK,SKY	
Discount Schedule	CS1	
GTIN	03389118041127	
Package weight(Lbs)	0.23 kg (0.5 lb(US))	
Returnability	No	
Country of origin	MX	

Offer Sustainability

Green Premium product	
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.p65warnings.ca.gov	
☑ REACh Declaration	
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Yes	
₫Yes	
China RoHS Declaration	
Product Environmental Profile	
No need of specific recycling operations	
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	


Contractual warranty

Warranty	18 months
----------	-----------

Product data sheet Dimensions Drawings

9001KP36LWW9

Dimensions



e panel thickness: 1 to 6 mm / 0.04 to 0.24 in.