

## Between Series Adaptor 33\_PC7-PC35-50-1/1--\_U

### Description

Adaptor plug/jack  
PC 7 plug (male) / PC 3.5 jack (female)

For Test & Measurement applications  
Precision adaptor

Interface standards  
Series PC 7 - IEEE STD 287\_ANSI C 16.43  
Series PC 3.5 - IEC 60169-23



### Technical Data

#### Electrical Data

Impedance	50 Ω	
Interface frequency max.	18 GHz	
Frequency range	DC to 15 GHz	15 to 18 GHz
Return loss	≥ 32 dB	≥ 27 dB
Electrical length	35.97 mm	

#### Mechanical Data

Number of matings	500
Weight	0.0476 kg

#### Environmental Data

Operating temperature	-55 °C to 70 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Interface - PC 7 plug (male)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer contact	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	Air Dielectric - Bead - PPH	
Coupling nut	Brass	SUCOPLATE (R) Plating

Interface - PC 3.5 jack (female)

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	Air Dielectric - Bead - PPH	

### Ordering Information

Single package	33_PC7-PC35-50-1/1--_UE
----------------	-------------------------

### Remarks

Operating specification acc. IEEE Std 287: temperature 13 °C to 33 °C

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[33\\_PC7-PC35-50-1/1--\\_UE](#)