

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# USB 3.1 Gen 1 (5 Gbps) Cable, USB Type-C (USB-C) to USB Type-A M/M, 3-ft. Length

MODEL NUMBER: U428-003



#### Description

The U428-003 USB 3.1 Gen 1 Cable connects a USB Type-C (USB-C) device to the USB Type-A port on your tablet, computer, or USB charger. The 3-foot cable supports data transfer speeds up to 5 Gbps. Unlike traditional USB cables that can be attached only one way, the reversible USB Type-C male connector plugs into

## **Highlights**

- Connects a USB Type-C (USB-C) device to the USB Type-A port on your tablet, computer, or USB charger
- Supports USB 3.1 Gen 1 data transfer speeds up to 5 Gbps
- Features reversible USB Type-C male plug on one end
- . Works with USB 3.0 devices

#### **System Requirements**

- A device with a USB Type-C (USB-C) port
- A device with a USB Type-A port

### **Package Includes**

 U428-003 USB 3.1 Gen 1 (5 Gbps) Cable, USB Type-C (USB-C) to USB Type-A M/M, 3 ft

a USB port in either direction for fast, fumble-free connection every time. Superior foil shielding provides reliable, error-free data communication. Nickel-plated molded end connectors and gold-plated copper contacts ensure superior conductivity and long life. Slim form supports evolving design trends toward smaller devices. Backward-compatible with USB 3.0 devices.

#### **Features**

Supports USB 3.1 Gen 1

- Data transfer speeds up to 5 Gbps—10 times faster than USB 2.0
- Uses same Type-A male connector as USB 3.0 devices
- USB Type-C (USB-C) Male Connector

USB Type-C (USB-C) Male Connector

- Fumble-free reversible plug ensures fast, easy connection every time
- Powerful enough for smartphones, tablets, computers and other larger platforms

Premium Construction

- Gold-plated copper contacts and nickel-plated molded ends provide a lifetime of heavy use and superior conductivity
- Superior foil shielding offers reliable, error-free data communication
- Slim, sleek design tailored for emerging design trends toward smaller devices

# **Specifications**

INPUT	
Cable Length (ft.)	3



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Cable Length (m)	0.9	
PHYSICAL		
Color	Black	
ENVIRONMENTAL		
Operating Temperature Range	14 to 140 F (-10 to 60 C)	
Storage Temperature Range	-4 to 185 F (-20 to 85 C)	
Relative Humidity	10 to 85%	
CONNECTIONS		
Side A - Connector 1	USB C (MALE)	
Side B - Connector 1	USB 3.0 A (MALE)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies