

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20




© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.



REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL RELEASE	08JUL2015	DL	CW




NOTES:
1. TECHNICAL CHARACTERISTICS:
BODY MATERIAL: DIE CAST ALUMINIUM ALLOY
SURFACE TREATMENT: POWDER-COATED, GRAY
OPERATION TEMPERATURE: -40-+125°C
DEGREE OF PROTECTION: IP65 (MATED)

注释:
1. 技术参数:
主体材料: 铝合金
表面处理: 粉末喷涂, 灰色
工作温度: -40-+125°C
防护等级: IP65(配合)



TI650103121-000	H10B-SGRH-LB-PG21	PG21	-
TI650103129-000	H10B-SGRH-LB-PG29	PG29	-
TI650103132-000	H10B-SGRH-LB-M32	M32	-
TI650103221-000	H10B-SGRH-LB-2PG21	PG21	PG21
TI650103225-000	H10B-SGRH-LB-2M25	M25	M25
TI650103229-000	H10B-SGRH-LB-2PG29	PG29	PG29
TI650103232-000	H10B-SGRH-LB-2M32	M32	M32
TI650102532-000	H10B-SGRH-LB-M25/M32	M25	M32
ASSEMBLY PART NUMBER	ASSEMBLY PART DESCRIPTION	IG1	IG2

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DAVID LI 08JUL2015	 TE Connectivity	
		CHK CHRIS WANG 08JUL2015		
		APVD XU XIANG 08JUL2015		
		PRODUCT SPEC 108-137013		
DIMENSIONS: mm		APPLICATION SPEC 114-137013	NAME H10B-SGRH-LB-PG/M	
		WEIGHT -		
MATERIAL TBD		CUSTOMER DRAWING	SIZE A3	CAGE CODE -
TOLERANCES UNLESS OTHERWISE SPECIFIED:			DRAWING NO	RESTRICTED TO
0 PLC ±-			SCALE 7:10	
1 PLC ±-			SHEET 1 OF 1	
2 PLC ±-			REV A	
3 PLC ±-				
4 PLC ±-				
ANGLES ±-				
FINISH -				