TO THIS PRODUCT. FOR DETAILS, PLEASE //BELFUSE.COM/STEWART/STEWART_PATENTS/	ONNECIOR AND SHALL NOI BE REPRODUCED, ISED IN ANY MANNER WITHOUT PRIOR WRITTEN EWART CONNECTOR, ONE OR MORE U.S. PATENTS	AND THE SUBJECT MATTER SHOWN THEREON NITAL AND THE PROPRIETARY PROPERTY OF
DWG NO.	APPD BY:	DRN BY:
CT820006	DHG	TRM
	DATE 7—	DATE 7—
REV. A9	^E 7–18–05	7-18-05

SHIELDED CABLE READY CATSE JACK (SHOWN IN TERMINATED CONDITION) guo http://www.stewartconnector.com 11118 Susquehanna Trail South Glen Rock, PA 17327—9199 (717) 235—7512

	TITLE.		
~ a bel gr			4
		† †	<u></u>
)		_
		ANGLE PROJECTION	THIRD

50 MICRO-INCHES [1.27um]

SS-82100-001

PART NUMBER

 \supset


CONTACT PLATING IN MATING AREA

		-	•		
SHEET NO. 1 OF 1	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ±.005 [0.13] ANGLES ARE ± 1°	DIMENSIONS: INCHES [METRIC]	DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE	DO NOT SCALE DRAWING	


RECOMMENDED PANEL OPENING 1.88] MAXIMUM PANEL THICKNESS	
FERRULE P/N F-270-205	.205 [5.21]

2


.685 [17.40]



 \supset



-	WRE STRAIN RELIEF
	0
0	



 ϖ

1.51 [38,35] 1.06 [26,93] MAX MAX .680 [17.27] MIN LOAD BAR					
7.27]	LOAD BAR			1.06 [26,93] MAX	1.51 [38,35] MAX
		580 [17.27] MIN	-		

WIRING - IDENTIFICATION LABEL

INSERTION DIRECTION


-PANEL

1. CONNECTOR MATERIALS:
HOUSING: THERMOPLASTIC UL94 V-0
CONTACTS/SHIELD: COPPER ALLOY
SHIELD PLATING: NICKEL
FERRULE PLATING: NICKEL OR TIN
CONTACT PLATING: SELECTIVE GOLD IN CONTACT AREA
SEE CHART FOR PART NUMBER

FOR PRODUCT SPECIFICATIONS SEE PRO26-01.
 DIMENSIONS AND TOLERANCES COMPLY WITH TIA-1096 STANDARD.

NOTES:

-9	
]	



 ϖ

11-14-17	3-29-16	DATE	
А9	A8	REV	
11149	10646	ECN	
TRM	TRM	APP'D. BY	