



DIP4-pin type with reinforced insulation

PhotoMOS®

**GE 1 Form A
(AQY210EH)**



RoHS compliant

FEATURES

1. Reinforced insulation of 5,000 V

More than 0.4 mm internal insulation distance between inputs and outputs. Conforms to EN41003, EN60950 (reinforced insulation).

2. Controls low-level analog signals

PhotoMOS feature extremely low closed-circuit offset voltage to enable control of low-level analog signals without distortion.

3. High sensitivity and low on-resistance

Can control max. 0.13 A load current with 5 mA input current.

Low on-resistance of Typ. 25Ω (AQY210EH).

4. Low-level off state leakage current of max. 1 µA

TYPICAL APPLICATIONS

- Modem
- Telephone equipment
- Electricity, plant equipment
- Security equipment
- Sensing equipment

TYPES

I/O isolation voltage		Output rating**		Package	Part No.			Packing quantity		
					Through hole terminal		Surface-mount terminal			
		Load voltage	Load current		Tape and reel packing style		Picked from the 1/2-pin side	Picked from the 3/4-pin side	Tube	Tape and reel
AC/DC dual use	Reinforced 5,000 Vrms				Tube packing style					
	30 V	1,000 mA	DIP4-pin	AQY211EH	AQY211EHA	AQY211EHAX	AQY211EHAZ	1 tube contains: 100 pcs. 1 batch contains: 1,000 pcs.	1,000 pcs.	
	60 V	550 mA		AQY212EH	AQY212EHA	AQY212EHAX	AQY212EHAZ			
	350 V	130 mA		AQY210EH	AQY210EHA	AQY210EHAX	AQY210EHAZ			
	400 V	120 mA		AQY214EH	AQY214EHA	AQY214EHAX	AQY214EHAZ			
	600 V	50 mA		AQY216EH	AQY216EHA	AQY216EHAX	AQY216EHAZ			

**Indicate the peak AC and DC values.

Note: For space reasons, the initial letters of the part number "AQY", the surface mount terminal shape indicator "A" and the packing style indicator "X" or "Z" are not marked on the device. (Ex. the label for product number AQY211EHAX is 211EH)

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)


Item	Symbol	AQY211EH(A)	AQY212EH(A)	AQY210EH(A)	AQY214EH(A)	AQY216EH(A)	Remarks
Input	LED forward current	I _F		50mA			
	LED reverse voltage	V _R		5 V			
	Peak forward current	I _{FP}		1 A			f =100 Hz, Duty factor = 0.1%
	Power dissipation	P _{in}		75mW			
Output	Load voltage (peak AC)	V _L	30 V	60 V	350 V	400 V	600 V
	Continuous load current	I _L	1 A	0.55 A	0.13 A	0.12 A	0.05 A
	Peak load current	I _{peak}	3 A	1.5 A	0.4 A	0.3 A	0.15 A
	Power dissipation	P _{out}		500mW			
Total power dissipation		P _T		550mW			
I/O isolation voltage		V _{iso}		5,000 Vrms			
Ambient temperature	Operating	T _{opr}		-40 to +85°C	-40 to +185°F		(Non-icing at low temperatures)
	Storage	T _{stg}		-40 to +100°C	-40 to +212°F		

GE 1 Form A (AQY21OEH)

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item		Symbol	AQY211EH(A)	AQY212EH(A)	AQY210EH(A)	AQY214EH(A)	AQY216EH(A)	Condition
Input	LED operate current	Typical	I _{Fon}	1.2mA				I _L =Max.
		Maximum		3.0mA				
	LED turn off current	Minimum	I _{Foff}	0.4mA				I _L =Max.
		Typical		1.1mA				
Output	LED dropout voltage	Typical	V _F	1.25 (1.14 V at I _F =5mA)				I _F =50mA
		Maximum		1.5V				
	On resistance	Typical	R _{on}	0.25Ω	0.85Ω	18Ω	26Ω	I _F =5mA
		Maximum		0.5Ω	2.5Ω	25Ω	35Ω	I _L =Max. Within 1 s
Transfer characteristics	Off state leakage current	Maximum	I _{Leak}	1μA				
	Turn on time*	Typical	T _{on}	1.5ms	1ms	0.5ms		I _F =5mA
		Maximum		5ms	4ms	2.0ms		I _L =Max.
	Turn off time*	Typical	T _{off}	0.1ms	0.05ms	0.08ms	0.04ms	I _F =5mA
		Maximum		1.0ms				I _L =Max.
	I/O capacitance	Typical	C _{iso}	0.8pF				f = 1MHz
		Maximum		1.5pF				V _B = 0V
	Initial I/O isolation resistance	Minimum	R _{iso}	1,000MΩ				500V DC

*Turn on/Turn off time



3. Recommended operating conditions (Ambient temperature: 25°C 77°F)

Please use under recommended operating conditions to obtain expected characteristics.


Item		Symbol	Min.	Max.	Unit
LED current		I _F	5	30	mA
AQY211EH(A)	Load voltage (Peak AC)	V _L	—	24	V
	Continuous load current	I _L	—	1	A
AQY212EH(A)	Load voltage (Peak AC)	V _L	—	48	V
	Continuous load current	I _L	—	0.55	A
AQY210EH(A)	Load voltage (Peak AC)	V _L	—	280	V
	Continuous load current	I _L	—	0.13	A
AQY214EH(A)	Load voltage (Peak AC)	V _L	—	320	V
	Continuous load current	I _L	—	0.12	A
AQY216EH(A)	Load voltage (Peak AC)	V _L	—	480	V
	Continuous load current	I _L	—	0.05	A

■ These products are not designed for automotive use.


If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

REFERENCE DATA


1-(1). Load current vs. ambient temperature characteristics
Allowable ambient temperature: -40 to +85°C
-40 to +185°F




1-(2). Load current vs. ambient temperature characteristics
Allowable ambient temperature: -40 to +85°C
-40 to +185°F




1-(3). Load current vs. ambient temperature characteristics
Allowable ambient temperature: -40 to +85°C
-40 to +185°F




2-(1). On resistance vs. ambient temperature characteristics
Measured portion: between terminals 3 and 4;
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




2-(2). On resistance vs. ambient temperature characteristics
Measured portion: between terminals 3 and 4;
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




2-(3). On resistance vs. ambient temperature characteristics
Measured portion: between terminals 3 and 4;
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




3-(1). Turn on time vs. ambient temperature characteristics
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




3-(2). Turn on time vs. ambient temperature characteristics
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




4-(1). Turn off time vs. ambient temperature characteristics
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




4-(2). Turn off time vs. ambient temperature characteristics
LED current: 5 mA; Load voltage: Max. (DC);
Continuous load current: Max. (DC)



5. LED operate current vs. ambient temperature characteristics
Sample: All types; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




6. LED turn off current vs. ambient temperature characteristics
Sample: All types; Load voltage: Max. (DC);
Continuous load current: Max. (DC)




GE 1 Form A (AQY21○EH)


7. LED dropout voltage vs. ambient temperature characteristics
Sample: All types; LED current: 5 to 50 mA




8-(1). Current vs. voltage characteristics of output at MOS portion
Measured portion: between terminals 3 and 4;
Ambient temperature: 25°C 77°F




8-(2). Current vs. voltage characteristics of output at MOS portion
Measured portion: between terminals 3 and 4;
Ambient temperature: 25°C 77°F




8-(3). Current vs. voltage characteristics of output at MOS portion
Measured portion: between terminals 3 and 4;
Ambient temperature: 25°C 77°F



9-(1). Off state leakage current vs. load voltage characteristics
Measured portion: between terminals 3 and 4;
Ambient temperature: 25°C 77°F




9-(2). Off state leakage current vs. load voltage characteristics
Measured portion: between terminals 3 and 4;
Ambient temperature: 25°C 77°F




10-(1). Turn on time vs. LED forward current characteristics

Measured portion: between terminals 3 and 4;
Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




10-(2). Turn on time vs. LED forward current characteristics

Measured portion: between terminals 3 and 4;
Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




11-(1). Turn off time vs. LED forward current characteristics

Measured portion: between terminals 3 and 4;
Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




11-(2). Turn off time vs. LED forward current characteristics

Measured portion: between terminals 3 and 4;
Load voltage: Max. (DC); Continuous load current: Max. (DC); Ambient temperature: 25°C 77°F




12-(1). Output capacitance vs. applied voltage characteristics

Measured portion: between terminals 3 and 4;
Frequency: 1 MHz; Ambient temperature: 25°C 77°F



12-(2). Output capacitance vs. applied voltage characteristics

Measured portion: between terminals 3 and 4;
Frequency: 1 MHz; Ambient temperature: 25°C 77°F



"PhotoMOS®", "PhotoMOS" and "PHOTOMOS" are registered trademarks of Panasonic Corporation.

*Recognized in Japan, the United States, all member states of European Union and other countries.

Please contact

Panasonic Corporation

Electromechanical Control Business Division

■ 1006, Oaza Kadoma, Kadomashi, Osaka 571-8506, Japan
industrial.panasonic.com/ac/e/

Panasonic®

©Panasonic Corporation 2017

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[AQY210EH](#) [AQY210EHA](#) [AQY212EH](#) [AQY214EH](#) [AQY211EHA](#) [AQY212EHA](#) [AQY210EHAX](#) [AQY210EHAZ](#)
[AQY211EH](#) [AQY211EHAX](#) [AQY211EHAZ](#) [AQY214EHAX](#) [AQY216EH](#) [AQY216EHA](#) [AQY214EHA](#) [AQY214EHAZ](#)
[AQY212EHAX](#) [AQY212EHAZ](#) [AQY216EHAZ](#) [AQY216EHAX](#)