





REV.	DATE	DESCRIPTION
NC	02/07/06	INITIAL RELEASE



RECOMMENDED
CABLE STRIPPING DIMS.



NOTE:

1. CRIMPED FERRULE
HEX CRIMP SIZE .213"
2. CRIMPED CONTACT PIN
HEX CRIMP SIZE .068"

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS	DATE	Amphenol Connex							
8						DRAWN	G.R.S.	02/07/06	PART DESCRIPTION BNC CRIMP PLUG (FOR RG-58/U, 141/U CABLE)						
7						CHECKED									
6						ISSUED									
5						SHEET	1 OF 1		PART NO. 112116-10						
4	FERRULE	COPPER	NICKEL	1											
3	CONTACT PIN	BRASS	GOLD	1				DWG. NO. 112116-10.DWG REV. NC SIZE A SCALE NA							
2	INSULATOR	TEFLON	NATURAL	1											
1	SHELL/BODY	BRASS	NICKEL	1											
	DESCRIPTION	MATERIAL	FINISH	QTY				CAD FILE		C:/112/112116-10.DWG					