# 9038AG1S6



#### Main

Device short name	A
Enclosure type	Standard environment enclosure indoor
Product specific application	Mechanically alternating the operation of two pumps or motors
Switch application	Standard

# Complementary

Electrical connection	Screw clamp terminal		
Material	Stainless steel float/rod Nitrile (Buna-N) seal ring		
Motor power hp	2 hp at 115 V AC for 3 phases 1 hp at 460/575 V AC for 3 phases 3 hp at 230 V AC for 1 phase 5 hp at 230 V AC for 3 phases 3 hp at 115 V AC for 1 phase	1 hp at 460/575 V AC for 3 phases 3 hp at 230 V AC for 1 phase 5 hp at 230 V AC for 3 phases	
Mounting support	Flange		
Number of poles	2		
Permissible voltage	<= 575 V AC		
Switch function	DPST		

## **Environment**

NEMA degree of protection	NEMA 1	

### Offer Sustainability

Not Green Premium product	Not Green Premium product
Will not be Compliant	Will not be Compliant
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the Stat of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Sta	teDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth

of California to cause birth defects or other reproductive defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

#### Contractual warranty

Warranty period	18 months	