

REVISIONS				
REV	ECN	DESCRIPTION	DATE	APPROVED
T		ELASTOMER GASKET OPTION ADDED	SEP 15/09	ZLJ
U		DETAIL H ADDED	JAN 14/10	ZLJ
V		NOTE #3 ADDED	JAN 13/11	ZLJ
Z		BOTTOM VIEW ADDED	NOV 22/12	ZLJ

FS1-SF1-1XXX

MOUNTING SCREW OPTION

- 1 = 8 mm MOUNTING SCREW SHIPPED BULK IN SAME TRAYS WITH CAGE ASSEMBLIES
2 = NO MOUNTING SCREW SUPPLIED
3 = 10 mm MOUNTING SCREW WITH LOCK WASHER SHIPPED BULK IN SAME TRAYS WITH CAGE ASSEMBLIES


GASKET OPTION

- E = STAINLESS STEEL EMI GASKET
F = FOAM, CHOMERICS SOFT SHIELD 4800, EMI GASKET
C = CONDUCTIVE ELASTOMER, CHOMERICS S6305


KEYING OPTION (SEE BELOW TABLE FOR FURTHER CLARIFICATION)

- 0 = NO KEY
1 = KEY #1
2 = KEY #2
3 = KEY #3
4 = KEY #4
5 = KEY #5
6 = KEY #6
7 = KEY #7
24 = KEY #2 AND #4
46 = KEY #4 AND #6


Key Option	Part Number	Description
0	FS1-SF1-10XX	No Key
1	FS1-SF1-11XX	SATA 'X' Cable
2	FS1-SF1-12XX	
3	FS1-SF1-13XX	
4	FS1-SF1-14XX	SAS Universal Port
5	FS1-SF1-15XX	
6	FS1-SF1-16XX	
7	FS1-SF1-17XX	SATA 'M' Cable
2, 4	FS1-SF1-124XX	SAS Out Port
4, 6	FS1-SF1-146XX	SAS In Port



PART NUMBER: **FS1-SF1-14C1** SHOWN
(CAGE ASSEMBLY WITH ELASTOMERIC GASKET
AND 8mm MOUNTING SCREWS SHIPPED BULK)



PART NUMBER: **FS1-SF1-14E1** SHOWN
(CAGE ASSEMBLY WITH STAINLESS STEEL
GASKET AND 8mm MOUNTING SCREWS SHIPPED BULK)








PART NUMBER: **FS1-SF1-14F1** SHOWN
(CAGE ASSEMBLY WITH FOAM GASKET
AND 8mm MOUNTING SCREWS SHIPPED BULK)



DO NOT SCALE DRAWING

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE
OR USED FOR MANUFACTURING PURPOSES WITHOUT PERMISSION FROM AMPHENOL CANADA CORP.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE:		APPROVALS		DATE		Amphenol Canada Corp.	
DECIMALS	ANGLES	DRAWN	ZLJ	JAN 6/09		TITLE	MINI SAS 0 DEGREE SINGLE PORT CAGE
.X ± 0.25	± 2°	DESIGNED	ZLJ	JAN 06/09			
.XX ± 0.10		CHECKED					
.XXX ± 0.05		QA APP'D					
MATERIAL AND FINISH							
ENG. REL. NO.	EAR 123XX	ENG. APP'D				SCALE	P-FS1-SF1-1XXX
CODE IDENT. NO.	03554	ENG. APP'D				NTS	SFF
						DWG. NO.	C
						REV	Z
						SHEET	1 OF 1



KEY #1


KEY #2

KEY #3


KEY #5

KEY #6


KEY #7







KEY #2, 4




KEY #4, 6




RECOMMENDED PANEL CUT-OUT

RECOMMENDED FACE PLATE TO
LOCATING POST DISTANCE

DETAIL H
SCALE 16 : 1



DETAIL G
SCALE 4 : 1



DO NOT SCALE DRAWING

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT PERMISSION FROM AMPHENOL CANADA CORP.



REVISIONS				
REV.	ECN	DESCRIPTION	DATE	APPROVE
2		SEE SHEET 1	FEB 22/12	ZLJ

NOTES:

1) MATERIAL:

MAIN CAGE: ZINC DIECAST SHELL WITH 150 MICROINCHES OF
NICKEL PLATING
EMC GASKET: SEE SHEET 1
COVER: STAINLESS STEEL
MOUNTING SCREW: AISI 1010 STEEL

2) ROHS COMPLIANT

3) COMPATIBLE WITH SFF-8088 SHIELDED MULTILANE MINI SAS PLUGS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE:		<table><tr><th>APPROVALS</th><th>DATE</th></tr><tr><td>DESIGNED ZLJ</td><td>JAN 06/09</td></tr><tr><td>DESIGNED ZLJ</td><td>JAN 06/09</td></tr><tr><td>CHECKED</td><td></td></tr><tr><td>QA APP'D</td><td></td></tr></table>		APPROVALS	DATE	DESIGNED ZLJ	JAN 06/09	DESIGNED ZLJ	JAN 06/09	CHECKED		QA APP'D		Amphenol Canada Corp.	
APPROVALS	DATE														
DESIGNED ZLJ	JAN 06/09														
DESIGNED ZLJ	JAN 06/09														
CHECKED															
QA APP'D															
DECIMALS X = 0.15 XX = 0.25 XXX = 0.05 MATERIAL AND FINISH		ANGLES ± 2°													
ENG. REL. NO. EAR 123XX		E APP'D													
CODE IDENT. NO. 03554		DWG APP'D													
		SCALE NTS		P-FSI-1FL-1XXX SINGLE PORT CAGE SHEET 1 OF 1											