

<p>0359</p> <p>0359-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>	<p>0358</p> <p>0358-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>	<p>0360</p> <p>0360-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>	<p>0343</p> <p>0343-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>
--	--	--	--

<p>0356</p> <p>0356-0-15-XX-34-XX-10-0 Solder mount in 2,59 min. mounting hole Also available on 24mm wide carrier tape: 1,100 parts per 330mm reel. Order as: 0356-0-57-XX-34-XX-10-0</p>	<p>6659</p> <p>6659-0-15-XX-34-XX-10-0 Solder mount in 2,59 min. mounting hole</p>	<p>0347</p> <p>0347-0-15-XX-34-XX-10-0 Solder mount in 3,05 min. mounting hole</p>	<p>0329</p> <p>0329-0-15-XX-34-XX-10-0 Solder mount in 1,91 min. mounting hole. "knock out" bottom.</p>
--	--	--	---

<p>0814</p> <p>0814-0-15-XX-34-XX-04-0 Solder mount in 2,08 min. mounting hole</p>	<p>5059</p> <p>5059-0-15-XX-34-XX-04-0 Press-fit in 2,29 mounting hole</p>	<p>8360</p> <p>8360-0-15-XX-34-XX-10-0 Press-fit in 2,21 mounting hole</p>	<p>9359</p> <p>9359-0-15-XX-34-XX-10-0 Press-fit in 2,29 mounting hole</p>
--	--	--	--

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±0,13 DIAMETERS: ±0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 15 - XX - 34 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <ul style="list-style-type: none"> 01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 15 0,25µm GOLD OVER NICKEL (RoHS) <p>SPECIFY CONTACT FINISH:</p> <ul style="list-style-type: none"> 01 5,08µm TIN/LEAD OVER NICKEL ◇ 80 5,08µm TIN OVER NICKEL (RoHS) ◇ 27 0,76µm GOLD OVER NICKEL (RoHS) <p style="text-align: center;">CONTACT</p> <p style="text-align: center;">#34 CONTACT (DATA ON PAGE 224)</p>
---	--