




POWER STRIP 40



(6.35 mm) .250"

PES, PET SERIES

40 A HIGH POWER HEADER & SOCKET

PES Mates with:
PET

PET Mates with:
PES, PESS

SPECIFICATIONS

For complete specifications see www.samtec.com?PET or www.samtec.com?PES

- Insulator Material:** Black LCP
- Terminal Material:** Copper Alloy
- Plating:** Sn or Au over 50 μ" (1.27 μm) Ni
- Operating Temp Range:** -55 °C to +105 °C with Tin, -55 °C to +125 °C with Gold
- Voltage Rating:** 725 VAC/1025 VDC
- Wiping Distance:** (4.14 mm) .163" Max
- Standard Creepage:** (3.66 mm) .144"
- Standard Clearance:** (3.31 mm) .130"
- RoHS Compliant:** Yes
- Lead-Free Solderable:** Yes

PET/PES	
PINS	CURRENT RATING (PER CONTACT)
1	58.7 A
2	48.5 A
3	41.1 A
4	38.0 A
8	29.4 A

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



FILE NO. E111394

ALSO AVAILABLE (MOQ Required)

- Locking Clip (Manual placement required)
- No Latch ears
- Other platings

OTHER SOLUTIONS

- Combination Signal/Power. See PES or PETC Series.

Note: Some sizes, styles and options are non-standard, non-returnable.

PES

NO. PINS PER ROW

-02, -04, -06, -08

LEAD STYLE	A
-01	(2.35) .093
-02	(3.95) .156

LEAD STYLE

-01
= Use with (1.60 mm) .062" Thick PCB

-02
= Use with (3.18 mm) .125" Thick PCB

PLATING OPTION

-L
= 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail

-T
= Matte Tin

TAIL OPTION

-VT
= Vertical

-RA
= Right-angle (Screw Down option required)

OTHER OPTION

-SD
= Screw Down (Right-angle only)

RUGGEDIZED BY SAMTEC

- Screw down (right-angle)

CREEPAGE AND CLEARANCE

Selectively loading contacts achieves customer specific creepage and clearance requirements.
Contact asp@samtec.com

PET

NO. PINS PER ROW

-02, -04, -06, -08

LEAD STYLE	A
-01	(2.35) .093
-02	(3.95) .156

LEAD STYLE

-01
= Use with (1.60 mm) .062" Thick PCB

-02
= Use with (3.18 mm) .125" Thick PCB

PLATING OPTION

-L
= 10 μ" (0.25 μm) Gold on contact, Matte Tin on tail

-T
= Matte Tin

TAIL OPTION

-VT
= Vertical

-RA
= Right-angle (Screw Down option required)

OTHER OPTION

-SD
= Screw Down (Right-angle only)

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM

All parts within this catalog are built to Samtec's specifications. Customer specific requirements must be approved by Samtec and identified in a Samtec customer-specific drawing to apply.