



STX-35332 Series Surface Mount 3.5mm Audio Jack

Features

- Offered in a 2-Pole or 3-Pole Version
- Used in devices such as audio equipment, cell phones, or digital still camera
- Complies with EIA Standards
- CSA/NRTL Certified File No. LR78160



Performance Specifications

Materials and Finish

Housing

High Temperature Thermoplastic, UL 94V-0 Rated

Terminals

Copper Alloy, Gold Plated



Electrical Characteristics

**Contact Resistance
Before Durability Test**
50 milliohms Max.

After Durability Test
100 milliohms Max.

Rated Voltage
16V DC

Rated Current
0.3 A

Insulation Resistance
100 Megohms Min. at 500V DC

Dielectric Strength
500V AC RMS for 1 Minute

Operating Temperature
-25°C to +70°C

AUDIO JACKS

STX-35332 Series

Documentation & Ordering Information

Kycon Part #

Part Number Builder

Series	Number of Pins	Threading Option	Color Option	Packaging
Series STX-35332 - Surface Mount 3.5mm Audio Jack	Number of Pins 3 Pin 4 Pin 5 Pin	Threading Option N - Non-Threaded	Color option Black - Standard	Packaging TR - Tape and Reel
Contact Kycon for PC99 color option minimum order may apply				

STX-35332 Dimensions

Dimensions in mm

STX-35332-3N-TR

