CT4024 8 kV High Voltage Probe

Datasheet

Overview:

The CT4024 is a 8 kV high voltage divider probe for use with both digital and analog oscilloscopes.

Kit Contents:

- Probe
- Hook tip
- Flat bar tip

Features:

- Input voltage of 8 kV (DC+ACpk)
- 40 MHz bandwidth
- Voltage dividing of 1000:1
- Frequency compensation





All specifications apply to the unit after a temperature stabilization time of 20 minutes over an ambient temperature range of 25 $^{\circ}$ C \pm 5 $^{\circ}$ C.

| Specifications | |
|----------------------------------|--|
| Maximum Input Voltage (CAT I) | 8 kV (DC + ACpk) 6 kVrms AC |
| Division Ratio | 1000:1 |
| Bandwidth | 40 MHz (-3 dB) |
| Compensation Range | 5 pF to 50 pF |
| Temperature Coefficient | ≤200 ppm/°C |
| Input Resistance | 100 MΩ ± 5% |
| Rise Time | ≤9 ns |
| DC Volts | ±3% (below 8 kV) |
| AC Volts | ±3% at 1 kHz ±3 dB 0 to 40 MHz |
| Cable Length | 6.6 ft (2 m) |
| Designed for Use in | Pollution Degree 2 |
| Operating Environment | 32°F to 122°F (0°C to 50°C) |
| Storage Temperature | -4°F to 158°F (-20°C to 70°C) |
| Humidity | ≤80% relative humidity at 104°F (40°C) |
| Dimensions | 8.3 in (21 cm) |
| Weight | 0.40 lbs (180 g) |
| Warranty | One-year warranty |

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: caltestelectronics.com

