

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0475901001

Status:

Active

Overview:

Consumer USB Products

Description:

Micro-USB AB Receptacle, Right Angle, Top Mount, Surface Mount, Lead-Free

Documents:

Drawing (PDF)

Product Specification PS-47589-001 (PDF)

Packaging Specification PK-47589-001 (PDF)

RoHS Certificate of Compliance (PDF)

Agency Certification

UL

E107635

General

Product Family

I/O Connectors

Series

47590

Application

Wire-to-Board

Comments

Signal contacts 1.0A, Power contacts 1.8A

Component Type

Receptacle

Electrical Model

Yes

Overview

Consumer USB Products

Product Name

USB 2.0

Type

Micro-AB

UPC

884982783737

Physical

Boot Color

N/A

Circuits (Loaded)

5

Circuits (maximum)

5

Color - Resin

Black

Durability (mating cycles max)

10000

Flammability

94V-0

Gender

Receptacle

Keying to Mating Part

Yes

Lock to Mating Part

No

Material - Metal

Copper Alloy

Material - Plating Mating

Gold

Material - Plating Termination

Gold

Material - Resin

High Temperature Thermoplastic

Net Weight

0.263/g

Number of Rows

1

Orientation

Right Angle

PCB Retention

None

Packaging Type

Embossed Tape on Reel

Panel Mount

No

Pitch - Mating Interface

0.65mm

Pitch - Termination Interface

0.65mm

Polarized to Mating Part

Yes

Ports

1

Surface Mount Compatible (SMC)

Yes

Temperature Range - Operating

-30°C to +85°C

Termination Interface: Style

Surface Mount

Waterproof / Dustproof

No

Electrical

Current - Maximum per Contact


1.8A, 1.0A

Grounding to Panel

Yes

Shield Type

Full Shield



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

Compliant

China RoHS

REACH SVHC

Not Contained Per
-ED/79/2015 (17
December 2015)

Halogen-Free

Status

Low-Halogen

Need more information on product
environmental compliance?

Email productcompliance@molex.com
Please visit the [Contact Us](#) section for any
non-product compliance questions.

China ROHS
ELV

Green Image
Not Relevant

Search Parts in this Series

47590 Series

Shielded	Yes
Voltage - Maximum	30V AC (RMS)

Solder Process Data

Duration at Max. Process Temperature (seconds)	010
Lead-freeProcess Capability	REFLOW
Max. Cycles at Max. Process Temperature	001
Process Temperature max. C	245

Material Info

Reference - Drawing Numbers

Electrical Model Document	EE-47590-001
Packaging Specification	PK-47589-001
Product Specification	PS-47589-001
S-Parameter Model	SP-47590-001
Sales Drawing	SD-47590-101

This document was generated on 06/10/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION