Printed-circuit board connector - MSTBVA 2,5/ 7-G-5,08 GY7035 - 1702821

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(http://phoenixcontact.com/download)

PCB headers, nominal current: 12 A, number of positions: 7, pitch: 5.08 mm, color: light gray, contact surface: Tin, mounting: Wave soldering

The figure shows a 10-position version of the product

Your advantages

- Maximum flexibility when it comes to device design – one header for connectors with different connection technologies
- Well-known mounting principle allows worldwide use
- Vertical connection enables multi-row arrangement on the PCB
- Closed contour for optimum stability of the plug-in connection

Key Commercial Data

Packing unit	50 pc
GTIN	4 046356 620161
GTIN	4046356620161

Technical data

Dimensions

Pitch	5.08 mm
Dimension a	30.48 mm
Height	12 mm
Length of the solder pin	3.9 mm
Pin dimensions	1 x 1 mm

General

Range of articles	MSTBVA 2,5/..-G
Rated voltage (III/3)	250 V
Connection in acc. with standard	EN-VDE

Printed-circuit board connector - MSTBVA 2,5/ 7-G-5,08 GY7035 - 1702821

Technical data

General

Nominal current I_N	12 A
Color	light gray
Number of positions	7

Standards and Regulations

Connection in acc. with standard	EN-VDE

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Diagram



Type: TFKC 2,5/...-ST-5,08 with MSTBVA 2,5/...-G-5,08

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC	EAC	B.01742

Phoenix Contact 2018 © - all rights reserved
http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
http://www.phoenixcontact.com