

Page
1 / 2

OPTIONS: INDICATOR /SUPP.DIODES

FREQUENCY RANGE
IMPEDANCE

: 50 Ohms

FREQUENCY (GHz)	0 - 1	1 - 2	2 - 3
V.S.W.R ≤	1.15	1.20	1.25
INSERT. LOSS ≤	0.15 dB	0.20 dB	0.25 dB
ISOLATION ≥	85 dB	80 dB	75 dB
AVER. POWER (*)	700 W	500 W	400 W

ACTUATOR

: FAILSAFE

NOMINAL CURRENT AT 25° C (±10%)

: 310 mA

ACTUATOR VOLTAGE (V_{CC})

: 12V (10.2 to 13V)

TERMINALS

: male D-sub 9 pins (4-40 UNC nuts)

INDICATOR RATING

: 1 W / 30 V / 100 mA

CONNECTORS

: N fem. per MIL C 39012

LIFE

```

: 1.000.000 cycles

```

SWITCHING TIME (nominal voltage; 25° C)

: < 15 ms

CONSTRUCTION

```
: splashproof
```

WEIGHT

: < 185 g


OPERATING TEMPERATURE RANGE

(°C) : -40 , +85

STORAGE TEMPERATURE RANGE

(°C) : -55 , +85

(* : average power at 25° C)



ISSUE 22. jan. 08