







REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	LEN1570234~239 LE31570210~215	2015/07/20	Yulong_wang	Change to Share Drawing.
C	LEN1680402~413	2016/08/09	Yulong_wang	Add 6Pin & IP69K.



Note:

- * $\varnothing$ Important Dimension.
- * $\triangle C$ Waterproof Rate: IP68, IP69K.
- * Housing: Nylon+GF, Black.
- * Female Pin: Copper Alloy, Gold Plated.
- * Shield: Zinc Alloy, Nickel Plated.
- * Ground Pin: Copper Alloy, Gold Plated.
- * Screw Nut: Zinc Alloy, Nickel Plated.
- * Panel O-Ring: Viton, Black.
- * Housing O-Ring: Viton, Green.
- * Rated Voltage: 3 & 4Pin 250V dc. or ac.
5Pin 60V dc. or ac.
6~12Pin 30V dc. or ac.
- * Rated Current: 3~5Pin 4A
6~8Pin 2A
10~12Pin 1.5A
- * Operating Temperature: -40~105°C
- * For Panel Thickness Max 4.5mm.
- * Recommended Nut Torque: 4~6 Kgf.cm.




Pin Assignment Front View

UNIT: mm				TITLE		ITEM NO		DRAWN BY		DATE	
TOLERANCE		.X ±0.25		SCALE		MSAS-XXPFFP-SF8XXX		Yulong_wang		2016-08-09	
.XX ±0.1		SIZE		2:1		A4		CHECKED BY		Jinhai	
.XXX ±0.05		SHEET		REV.		1		APPROVED BY		Jerry	
ANGLES ±1°		WC-REV.		C		A.5		DATE		2016-08-09	
						$\varnothing$: Inspection item		ALTW			

Amphenol LTW
安費諾亮泰企業股份有限公司

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.



M SAS - XX P F F P - S F 8 XXX

SAS: A-Code Shielded

03: 3Pin
04: 4Pin
05: 5Pin
06: 6Pin
08: 8Pin
10: 10Pin
12: 12Pin


P: Panel (板端)
F: Female Connector (母座)

001: PG9
002: M16*1.5


8: IP68/69K (防水等級68/69K)

F: Front Fasten (前鎖式/Enclosure Rear Mount)
S: Screw (螺紋式)


P: PCB THT/DIP Type (180° 基板插件式)
F: Female Pin (母Pin)




PCB Layout (10P)




PCB Layout (12P)




PCB Layout (3P)




PCB Layout (4P)



PCB Layout (5P)



PCB Layout (6P)



PCB Layout (8P)

UNIT:mm				TITLE		ITEM NO		DRAWN BY		DATE	
TOLERANCE		.X ±0.25		SCALE		DWG NO		Yulong_wang		2016-08-09	
.XX ±0.1		SIZE		2:1		MSAS-XXPFFP-SF8XXX		CHECKED BY		DATE	
.XXX ±0.05		A4		REV.		CUSTOMER		Jinhai		2016-08-09	
ANGLES ±1°		WC-REV.		C		ALTW		APPROVED BY		DATE	
		A.4						Jerry		2016-08-09	
		QC: Inspection item									

Amphenol LTW
安費諾亮泰企業股份有限公司