

### Turn-Tell® Labels



- Innovative label design allows labels to rotate for visibility from any angle, and for repositioning on the wire/cable to align legends and improve aesthetics
- Labels can be easily installed on existing terminated wires and assemblies without disconnecting the wires/cables

- Available in P1™ Label Cassettes for the LS8E or LS8EQ printers and in computer printable rolls, for use with Easy-Mark™ Labeling Software and desktop thermal transfer printers
- Temperature range: -40°F to 200°F (-40°C to 93°C)



| Part Number | Part Description  | Width |      | Length |      | Print-On Area Height |      | Min. Cable O.D. |     | Max. Wire O.D. |     | Std. Pkg. Qty. | Std. Ctn. Qty. |
|-------------|---|-------|------|--------|------|----------------------|------|-----------------|-----|----------------|-----|----------------|----------------|
|             |   | In.   | mm   | In.    | mm   | In.                  | mm   | In.             | mm  | In.            | mm  |                |                |
| R050X075V1T | Thermal Transfer, Vinyl, 0.50" W x 0.75" H, 0.25" POA, Clear/White, 3" Core, 18 – 14 AWG wire/cable.  | 0.50  | 12.7 | 0.75   | 19.1 | 0.25                 | 6.4  | 0.12            | 3.1 | 0.16           | 4.1 | 5000           | 20000          |
| R050X125V1T | Thermal Transfer, Vinyl, 0.50" W x 1.25" H, 0.38" POA, Clear/White, 3" Core, 12 – 10 AWG wire/cable, Cat. 3 UTP cable.                      | 0.50  | 12.7 | 1.25   | 31.8 | 0.38                 | 9.7  | 0.12            | 3.1 | 0.16           | 4.1 | 5000           | 20000          |
| R050X150V1T | Thermal Transfer, Vinyl, 0.50" W x 1.50" H, 0.50" POA, Clear/White, 3" Core, 10 – 6 AWG wire/cable, Cat. 5e/6/6e UTP and Cat. 5e FTP cable. | 0.50  | 12.7 | 1.50   | 38.1 | 0.50                 | 12.7 | 0.16            | 4.0 | 0.32           | 8.1 | 5000           | 20000          |
| R100X075V1T | Thermal Transfer, Vinyl, 1.00" W x 0.75" H, 0.25" POA, Clear/White, 3" Core, 18 – 14 AWG wire/cable.  | 1.00  | 25.4 | 0.75   | 19.1 | 0.25                 | 6.4  | 0.12            | 3.1 | 0.16           | 4.1 | 2500           | 10000          |
| R100X125V1T | Thermal Transfer, Vinyl, 1.00" W x 1.25" H, 0.38" POA, Clear/White, 3" Core, 12 – 10 AWG wire/cable, Cat. 3 UTP cable.                      | 1.00  | 25.4 | 1.25   | 31.8 | 0.38                 | 9.7  | 0.16            | 4.1 | 0.22           | 5.6 | 2500           | 10000          |
| R100X150V1T | Thermal Transfer, Vinyl, 1.00" W x 1.50" H, 0.50" POA, Clear/White, 3" Core, Cat. 5e/6/6A UTP/Cat. 5e FTP cable.                            | 1.00  | 25.4 | 1.50   | 38.1 | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.1 | 2500           | 10000          |
| R100X150V2T | Thermal Transfer, Vinyl, 1.00" W x 1.50" H, 0.50" POA, Clear/Blue, 3" Core, Cat. 5e/6/6A UTP/Cat. 5e FTP cable.                             | 1.00  | 25.4 | 1.50   | 38.1 | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.1 | 2500           | 10000          |
| R100X150V3T | Thermal Transfer, Vinyl, 1.00" W x 1.50" H, 0.50" POA, Clear/Green, 3" Core, Cat. 5e/6/6A UTP/Cat. 5e FTP cable.                            | 1.00  | 25.4 | 1.50   | 38.1 | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.1 | 2500           | 10000          |
| R100X150V7T | Thermal Transfer, Vinyl, 1.00" W x 1.50" H, 0.50" POA, Clear/Red, 3" Core, Cat. 5e/6/6A UTP/Cat. 5e FTP cable.                              | 1.00  | 25.4 | 1.50   | 38.1 | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.1 | 2500           | 10000          |
| R100X150V8T | Thermal Transfer, Vinyl, 1.00" W x 1.50" H, 0.50" POA, Clear/Yellow, 3" Core, Cat. 5e/6/6A UTP/Cat. 5e FTP cable.                           | 1.00  | 25.4 | 1.50   | 38.1 | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.1 | 2500           | 10000          |
| R100X225V1T | Thermal Transfer Vinyl, 1.00" W x 2.25" H, 0.75" POA, Clear/White, 3" Core, 8 – 4 AWG wire/cable, Cat. 6A UTP, FTP/Cat. 6 FTP cable.        | 1.00  | 25.4 | 2.25   | 57.2 | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9 | 2500           | 10000          |
| R100X225V2T | Thermal Transfer, Vinyl, 1.00" W x 2.25" H, 0.75" POA, Clear/Blue, 3" Core, 8 – 4 AWG wire/cable, Cat. 6A UTP, FTP/Cat. 6 FTP cable.        | 1.00  | 25.4 | 2.25   | 57.2 | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9 | 2500           | 10000          |
| R100X225V3T | Thermal Transfer, Vinyl, 1.00" W x 2.25" H, 0.75" POA, Clear/Green, 3" Core, 8 – 4 AWG wire/cable, Cat. 6A UTP, FTP/Cat. 6 FTP cable.       | 1.00  | 25.4 | 2.25   | 57.2 | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9 | 2500           | 10000          |
| R100X225V7T | Thermal Transfer, Vinyl, 1.00" W x 2.25" H, 0.75" POA, Clear/Red, 3" Core, 8 – 4 AWG wire/cable, Cat. 6A UTP, FTP/Cat. 6 FTP cable.         | 1.00  | 25.4 | 2.25   | 57.2 | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9 | 2500           | 10000          |
| R100X225V8T | Thermal Transfer, Vinyl, 1.00" W x 2.25" H, 0.75" POA, Clear/Yellow, 3" Core, 8 – 4 AWG wire/cable, Cat. 6A UTP, FTP/Cat. 6 FTP cable.      | 1.00  | 25.4 | 2.25   | 57.2 | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9 | 2500           | 10000          |

Order number of labels required in multiples of Std. Pkg. Qty.

**Turn-Tell<sup>®</sup> Labels (continued)**

| Part Number        | Part Description  | Width |      | Length |       | Print-On Area Height |      | Min. Cable O.D. |     | Max. Wire O.D. |      | Std. Pkg. Qty. | Std. Ctn. Qty. |
|--------------------|---|-------|------|--------|-------|----------------------|------|-----------------|-----|----------------|------|----------------|----------------|
|                    |   | In.   | mm   | In.    | mm    | In.                  | mm   | In.             | mm  | In.            | mm   |                |                |
| <b>R100X400V1T</b> | Thermal Transfer, Vinyl, 1.00" W x 4.00" H, 1.00" POA, Clear/White, 3" Core, 2 AWG – 250 MCM wire/cable.                              | 1.00  | 25.4 | 4.00   | 101.6 | 1.00                 | 25.4 | 0.39            | 9.9 | 0.95           | 24.1 | 1000           | 4000           |
| <b>R200X150V1T</b> | Thermal Transfer, Vinyl, 2.00" W x 1.50" H, 0.50" POA, Clear/White, 3" Core, Cat. 5e/6/6A UTP/Cat. 5e FTP cable.5/5e/6 cable.         | 2.00  | 50.8 | 1.50   | 38.1  | 0.50                 | 12.7 | 0.22            | 5.6 | 0.28           | 7.1  | 1000           | 4000           |
| <b>R200X225V1T</b> | Thermal Transfer, Vinyl, 2.00" W x 2.25" H, 0.75" POA, Clear/White, 3" Core, 8 – 4 AWG wire/cable, Cat. 6A UTP, FTP/Cat. 6 FTP cable. | 2.00  | 50.8 | 2.25   | 57.2  | 0.75                 | 19.1 | 0.28            | 7.1 | 0.39           | 9.9  | 1000           | 4000           |
| <b>R200X400V1T</b> | Thermal Transfer, Vinyl, 2.00" W x 4.00" H, 1.00" POA, Clear/White, 3" Core, 2 AWG – 250 MCM wire/cable.                              | 2.00  | 50.8 | 4.00   | 101.6 | 1.00                 | 25.4 | 0.39            | 9.9 | 0.95           | 24.1 | 1000           | 4000           |

Order number of labels required in multiples of Std. Pkg. Qty.

**Thermal Transfer Marker Plates**


- Non-adhesive marker plates offer crisp, clear legends with superior legibility
- Attachable in a horizontal or vertical orientation
- Available in a variety of colors and sizes

- Use with Panduit RMER4BL resin thermal transfer ribbon, found on O.13
- Temperature range: -58°F to 221°F (-50°C to 105°C)

| Part Number      | Color  |       |      |       |      |        |     | Width In. (mm) | Height In. (mm) | Print-On Area In. (mm) | Labels Per Roll | Std. Pkg. Qty. |
|------------------|--------|-------|------|-------|------|--------|-----|----------------|-----------------|------------------------|-----------------|----------------|
|                  | Yellow | White | Blue | Green | Gray | Orange | Red |                |                 |                        |                 |                |
| <b>M200X050*</b> | Y6T    | Y7T   | ACT  | AET   | AFT  | AGT    | AIT | 2.00 (50.8)    | 0.50 (12.7)     | 1.07 (27.2)            | 500             | 1 Roll         |
| <b>M200X100*</b> | Y6T    | Y7T   | ACT  | AET   | AFT  | AGT    | AIT | 2.00 (50.8)    | 1.00 (25.4)     | 0.80 (20.3)            | 500             | 1 Roll         |
| <b>M300X050*</b> | Y6T    | Y7T   | ACT  | AET   | AFT  | AGT    | AIT | 3.00 (76.2)    | 0.50 (12.7)     | 1.80 (52.6)            | 500             | 1 Roll         |
| <b>M300X100*</b> | Y6T    | Y7T   | ACT  | AET   | AFT  | AGT    | AIT | 3.00 (76.2)    | 1.00 (25.4)     | 1.80 (45.7)            | 500             | 1 Roll         |

Replace the asterisk in part numbers above with the desired color code.

## **NEW!** Thermal Transfer Flag Labels



- Improved legibility and more information on small wires and cables provide clearer, more complete identification
- Innovative design allows the product to be applied as a permanent adhesive label or as a repositionable non-adhesive label
- Easy-Mark<sup>™</sup> Labeling Software assists in the creation of optimum identifiers and labels for common labeling applications, advanced importing and barcoding capability to assist in reducing errors and saving time

| Part Number        | Color | Width |      | Height |      | Min. Cable O.D. |     | Max. Cable O.D. |      | Wire Range  | Std. Pkg. Qty. | Std. Ctn. Qty. |
|--------------------|-------|-------|------|--------|------|-----------------|-----|-----------------|------|-------------|----------------|----------------|
|                    |       | In.   | mm   | In.    | mm   | In.             | mm  | In.             | mm   |             |                |                |
| <b>F100X150AJT</b> | White | 1.00  | 25.4 | 1.50   | 38.1 | 0.12            | 3.1 | 0.20            | 5.1  | 12 – 10 AWG | 2500           | 10000          |
| <b>F100X213AJT</b> | White | 1.00  | 25.4 | 2.13   | 54.1 | 0.32            | 8.1 | 0.38            | 9.7  | 3 – 2 AWG   | 2500           | 10000          |
| <b>F100X300AJT</b> | White | 1.00  | 25.4 | 3.00   | 76.2 | 0.90            | 2.3 | 0.28            | 7.1  | 18 – 6 AWG  | 2500           | 10000          |
| <b>F100X363AJT</b> | White | 1.00  | 25.4 | 3.63   | 92.2 | 0.20            | 5.1 | 0.46            | 11.7 | 8 – 1 AWG   | 2500           | 10000          |

Order number of pieces required, in multiples of Standard Package Quantity.

Prime items appear in **BOLD**.