

Memory - SD FLASH 2GB - 2988162

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Program and configuration memory



Product Features

- Program and configuration memory, plug-in, 2 Gbytes
- For storing application programs and other files in the file system of the PLC

Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	9.2 GRM
Custom tariff number	85235110
Country of origin	Taiwan

Technical data

Product type	Parameterization memory
--------------	-------------------------

Classifications

eCl@ss

eCl@ss 4.0	27240403
eCl@ss 4.1	27240403
eCl@ss 5.0	27242212
eCl@ss 5.1	27242212
eCl@ss 6.0	19150702
eCl@ss 7.0	19150702
eCl@ss 8.0	19150702

ETIM

ETIM 3.0	EC000192
ETIM 4.0	EC000192

Memory - SD FLASH 2GB - 2988162

Classifications

ETIM

ETIM 5.0	EC001068
----------	----------

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	32101601
UNSPSC 13.2	32101601

Accessories

Accessories

Controller

Controller - ILC 131 ETH - 2700973



The controller enables integration of I/O signals from MODBUS periphery devices into the control program via MODBUS/TCP. Programming takes place with PC Worx Express or PC Worx (IEC 61131-3).

Controller - ILC 131 ETH/XC - 2701034



Inline controller for use under harsh ambient conditions, with Ethernet interface for coupling to other controllers and systems, with programming options according to IEC 61131-3, complete with connector plug and labeling field.

Controller - ILC 151 ETH - 2700974



The controller enables integration of I/O signals from MODBUS periphery devices into the control program via MODBUS/TCP. Programming takes place with PC Worx Express or PC Worx (IEC 61131-3).

Memory - SD FLASH 2GB - 2988162

Accessories

Controller - ILC 151 ETH/XC - 2701141



Inline controller for use under harsh ambient conditions, with Ethernet interface for coupling to other controllers and systems, with programming options according to IEC 61131-3, complete with connector plug and labeling field.

Controller - ILC 171 ETH 2TX - 2700975



The controller enables integration of I/O signals from MODBUS periphery devices into the control program via MODBUS/TCP. Programming takes place with PC Worx Express or PC Worx (IEC 61131-3).

Controller - ILC 191 ETH 2TX - 2700976



The controller enables integration of I/O signals from MODBUS periphery devices into the control program via MODBUS/TCP. Programming takes place with PC Worx Express or PC Worx (IEC 61131-3).

Controller - ILC 191 ME/AN - 2700074



Inline controller with integrated pulse/direction interface, RS-485/RS-422, analog inputs (0 ... 10 V), and analog outputs (0 ... 10 V), with programming options according to IEC 61131-3

Controller - ILC 191 ME/INC - 2700075



Inline controller with integrated pulse/direction interface, RS-485/RS-422, fast counters, and incremental encoder inputs, with programming options according to IEC 61131-3

Memory - SD FLASH 2GB - 2988162

Accessories

Controller - AXC 1050 - 2700988



Axio control for direct open-loop control of Axioline I/Os. With 2 Ethernet interfaces and programming capabilities according to IEC 61131-3. Complete with connector plug and labeling field.

Controller - AXC 1050/XC - 2701295



Axiocontrol for the direct control of Axioline I/Os. With 2 Ethernet interfaces, extended temperature range, and programming options according to IEC 61131-3. Complete with connector plug and marking field.
