

## Coaxial Cable Connector 25\_4310-50-2-1/003\_-

### Description

Straight panel cable jack, flange mount

Interface standards

IEC 61169-54



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	12 GHz

#### Mechanical Data

Centre contact	plugged
Outer contact	soldered
Weight	0.0441 kg

#### Environmental Data

Operating temperature	-55 °C to 90 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Silver Plating
Outer contact	Bronze	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Other body part	Brass	Silver Plating
Insulator	PTFE (Polytetrafluoroethylene)	

### Related Documents

Outline drawing	DOU-00259221
Catalogue drawing	DCA-00264985
Assembly instruction	DOC-0000451466

### Ordering Information

Tray package	25_4310-50-2-1/003_-Y
Single package	25_4310-50-2-1/003_-E

### Additional Information

Suitable cables	SUCOFORM_86, EZ_86_M17
-----------------	------------------------

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[25\\_4310-50-2-1/003\\_-Y](#)