

LUMOTAST 16 - Emergency stop pushbutton, gold contacts, not illuminable, 1 NC, reset by rotation

1.15.213.011/0000



General information

| | |
|----------------|-----------------------|
| Form of lens | conical mushroom form |
| Color of lens | red |
| Form of collar | round |

Dimensions

| | |
|-------------------|---------|
| Mushroom Diameter | 30 mm |
| Overall height | 22.6 mm |
| Mounting depth | 18.2 mm |
| Mounting hole | 16.2 mm |

Mechanical design

| | |
|---------------------|---|
| Mounting | ring nut |
| Terminals | quick connector 2.8 x 0.5 mm, solderable / partially insulated connectors |
| Torque for nut ring | 1.0 - 1.5 Nm |
| Contact function | latching |
| Contact arrangement | 1 NC |
| Illuminability | no |
| Reset | by rotation |

Mechanical characteristics

| | |
|-----------------|-------|
| Robustness max. | 100 N |
|-----------------|-------|

Other specifications

| | |
|--------------------------------------|--|
| Ambient temp. operating min. | -25 °C |
| Ambient temp. operating max. | +70 °C |
| Robustness | acc. to IEC 600 68-2-3 und 2-30 |
| Operating life (operations) / B10 | 30,000 cycle |
| Degree of protection from front side | IP65 (DIN EN 60529) / IP67 |
| Storage temperature min. | -40 °C |
| Storage temperature max. | +80 °C |
| Environmental resistance | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Salt spray | IEC 600 68-2-11 |
| ROHS compliant | yes |
| REACH compliant | yes |

Panel cut-out

