



## Main

Range of product	Modicon M221
Product or component type	Serial line cartridge
Product compatibility	Modicon M221C

## Complementary

Integrated connection type	Non isolated serial link screw terminal block (RS232) Non isolated serial link screw terminal block (RS485)
Transmission rate	1.2115.2 kbit/s (115.2 kbit/s by default), bus length = 15 m (RS485) 1.2115.2 kbit/s (115.2 kbit/s by default), bus length = 9.84 ft (3 m) (RS232)
Communication port protocol	Modbus non isolated serial link master/slave (RTU/ASCII or SoMachine-Network)
Insulation	Non-insulated between lines and internal logic
Height	1.61 in (41 mm)
Depth	0.59 in (15 mm)
Width	1.38 in (35 mm)
Product weight	0.03 lb(US) (0.015 kg)

## **Environment**

## Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1415 - Schneider Electric declaration of conformity	Compliant - since 1415 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov