



### Main

|                           |               |
|---------------------------|---------------|
| Range of product          | Harmony 9001K |
| Product or component type | Pilot light   |
| Device short name         | 9001K         |

### Complementary

|                                                          |                                                                                       |
|----------------------------------------------------------|---------------------------------------------------------------------------------------|
| Bezel material                                           | Chromium plated metal                                                                 |
| Mounting diameter                                        | 1.18 in (30 mm)                                                                       |
| Shape of signaling unit head                             | Round                                                                                 |
| Lens type                                                | Domed (plastic)                                                                       |
| Cap/operator or lens colour                              | Red                                                                                   |
| Light source                                             | Incandescent                                                                          |
| Bulb base                                                | BA 9s                                                                                 |
| Light block supply                                       | Via integral transformer (f = 50/60 Hz) (secondary voltage = 6 V)                     |
| Connections - terminals                                  | Screw clamp terminals (1 x 0.22...2 x 1.5 mm <sup>2</sup> ) conforming to IEC 60947-1 |
| Tightening torque                                        | 7.08 lbf.in (0.8 N.m) conforming to IEC 60947-1                                       |
| Shape of screw head                                      | Cross slotted                                                                         |
| Shape of screw head                                      | Cross slotted head                                                                    |
| Operating position                                       | Any position                                                                          |
| [U <sub>i</sub> ] rated insulation voltage               | 250 V (degree of pollution: 2) conforming to IEC 60947-1                              |
| [U <sub>imp</sub> ] rated impulse withstand voltage      | 2.5 kV conforming to IEC 60947-1                                                      |
| Short-circuit protection                                 | 10 A cartridge fuse conforming to IEC 60947-5-1                                       |
| Light source                                             | Incandescent                                                                          |
| [I <sub>th</sub> ] conventional free air thermal current | 10 A                                                                                  |
| CAD overall width                                        | 2.13 in (54 mm)                                                                       |
| CAD overall height                                       | 2.76 in (70 mm)                                                                       |
| CAD overall depth                                        | 1.65 in (42 mm)                                                                       |
| [U <sub>s</sub> ] rated supply voltage                   | 220...240 V AC                                                                        |
| Product weight                                           | 0.46 lb(US) (0.21 kg)                                                                 |
| Device presentation                                      | Complete product                                                                      |

### Environment

|                                       |                                                                                                                |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|
| standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>JIS C 4520<br>JIS C 852<br>UL 508<br>CSA C22.2 No 14 |
| product certifications                | NEMA<br>UL 508                                                                                                 |
| protective treatment                  | TC                                                                                                             |
| ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                     |
| ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                                     |
| vibration resistance                  | 7 gn (f = 2...500 Hz) conforming to IEC 60068-2-6                                                              |

|                           |                                                                                 |
|---------------------------|---------------------------------------------------------------------------------|
| shock resistance          | 50 gn conforming to IEC 60068-2-27                                              |
| overvoltage category      | Class II conforming to IEC 61140                                                |
| IP degree of protection   | IP66 conforming to IEC 60529                                                    |
| NEMA degree of protection | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 6 |

Offer Sustainability

|                                                                                                                                  |                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| 785901820550                                                                                                                     | 785901820550                                                                                                                     |
| Compliant - since 0921 - Schneider Electric declaration of conformity                                                            | Compliant - since 0921 - Schneider Electric declaration of conformity                                                            |
| Reference not containing SVHC above the threshold                                                                                | Reference not containing SVHC above the threshold                                                                                |
| WARNING: This product can expose you to chemicals including:                                                                     | WARNING: This product can expose you to chemicals including:                                                                     |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

Contractual warranty

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Dimensions

