



No. of pos.	A <sup>+0.3</sup> <sub>-0.1</sub>	B <sup>±0.2</sup>	C <sup>+0.3</sup> <sub>-0.2</sub>	D <sup>+0.3</sup> <sub>-0.5</sub>	E <sup>±0.2</sup>	ØF cable diameter		Part-NO.
						WITH PRESS INSERT *	WITHOUT PRESS INSERT *	
9	32.9	25.0	39.5	41.9	16.4	4.0 - 6.3	6.4 - 8.6	165X13419X
15	41.2	33.3	45.5	47.9	16.4	4.0 - 6.3	6.4 - 8.6	165X13429X
25	54.9	47.0	52.5	54.9	16.4	6.5 - 8.5	8.6 - 12.0	165X13439X
37	71.4	63.5	55.0	57.9	18.8	8.5 - 10.9	11.0 - 14.0	165X13449X
50	69.0	61.1	55.0	57.9	19.6	8.5 - 10.9	11.0 - 14.0	165X13459X

\*) \* = WHICH INSERT IS USED IS ALSO DEPENDENT ON THE CABLE ITSELF

HOOD ASSEMBLY CONSISTS OF:

- 1 x HOOD + COVER: PBT UL 94 V-0; BLACK
- 1 x PRESS INSERT: PBT UL 94 V-0; BLACK
- 2 x JACKSCREWS: BRASS; NICKEL PLATED
- 2 x SCREW FOR STRAIN RELIEF: STEEL; NICKEL PLATED
- 1 x COVER SCREW (9-25pos.): STEEL; NICKEL PLATED
- 2 x COVER SCREW (37-50pos.): STEEL; NICKEL PLATED
- 1 x STRAIN RELIEF: STEEL; NICKEL PLATED

TECHNICAL DATA:

- TEMPERATURE RANGE: -33°C to +90°C
- ⊗ - RECOMMENDED MOUNTING TORQUE FOR STRAIN RELIEF SCREW + COVER SCREW: 0.15 Nm

RoHS compliant

APPROVAL \* FREIGABE \* DEBLOCAGE \* AUTORIZACION \* APPROVAL

CUSTOMER APPROVAL DATE:

NAME: TITLE:

COMPANY NAME:

APPROVAL \* FREIGABE \* DEBLOCAGE \* AUTORIZACION \* APPROVAL

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY, WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name
2 x e	Ä19-0215	22.07.2019	JLE
1 x d	Ä6896	04.10.2017	Lehmen
2 x c	Ä3644	12.05.2010	Petker
3 x b	Ä2196	04.04.2005	Lehmen
a	Original		

tolerance		scale: 1:1	
2000	date	material: SEE DRAWING	
drawn	26.06.	name	
appd.	26.06.	title: PLASTIC HOOD 9-50pos. with side cable exit	
norm		dwg no: AutoCAD	
d-old		DIN-A 3	
		sh: 1/1	
		part no: SEE TABLE	

**CONEC**