

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD

D

C

B

A

REPLACED BY OCEAN STYLE APPLICATOR PART NUMBER

FOR REPLACEMENT PARTS FOR APPLICATOR REFER TO ADDITIONAL PAGE(S). SPARE PARTS KIT (IF LISTED) WILL REMAIN AVAILABLE.

THE REPLACEMENT OCEAN STYLE APPLICATOR HAS THE SAME TERMINATOR/PRESS INTERFACE AS APPLICATOR

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:



TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	±
1 PLC	±
2 PLC	±
3 PLC	±
4 PLC	±
ANGLES	±

MATERIAL

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

TE Connectivity

NAME

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

C-

SCALE

SHEET OF

REV

1470-19 (3/11)

Pro/ENGINEER DRAWING

—	1	1	1	1	1	1	1528228	PRINT, APPLICATOR LOG SHEET	73
—	1	1	1	1	1	1	1338705-3	DOCUMENTATION PACKAGE	72
									71
									70
									69
									68
—	1	1	1	1	1	1	461264-5	PLATE, IDENTIFICATION	67
—	2	2	2	2	2	2	21017-2	SCR,DRIVE(#2x.19)ID PLATE	66
									65
									64
—	1	1	1	1	1	1	3-18031-0	SCR,SKT SET(M6X6)RAM	63
									62
—	2	2	2	2	2	2	2-18032-5	SCR,SET(M5X20)DRAG	61
—	1	1	1	1	1	1	18024-7	SCR,BHC(M4X10)ANVIL	60
—	1	1	1	1	1	1	5-18022-2	SCR,HEX(M4X8)FEED FINGER	59
									58
									57
—	1	1	1	1	1	1	1338685-1	PAWL, FEED	56
									55
—	4	4	4	4	4	4	18024-8	SCR,BHC(M4x12)SHEAR HOLDER	54
—	2	2	2	2	2	2	1-18023-3	SCR,SHC(M4x16)TERM HLD DWN	53
—	1	1	1	1	1	1	18030-1	NUT,HEX(M3)HOLD DOWN	52
—	1	1	1	1	1	1	811242-5	BUMPER, HOLDDOWN	51
—	1	1	1	1	1	1	690753-2	SPACER, TONKER	50
—	1	1	1	1	1	1	18024-3	SCR,BHC(M3X10)CAM	49
—	—	1	—	—	1	—	1338675-1	CAM, PRE FEED 30 & 40 mm ST	48
—	1	—	1	1	—	1	1338676-1	CAM, POST FEED 30 & 40 mm ST	47
—	1	1	1	1	1	1	1320999-3	APPLICATOR BASIC SUBASSY	46
—	1	1	1	1	1	1	690191-1	PLUG, NYLON	45
—	1	1	1	1	1	1	1338660-1	RAM	44
									43
									42
—	1	1	1	1	1	1	2-18024-6	SCR,BHC(M8X25)RAM	41
									40
—	1	1	1	1	1	1	690125-1	SHIM SUBASSY	39
									38
—	1	1	1	1	1	1	879103-3	FINE ADJUST HEAD SUBASSY	37
									36
									35
—	1	1	1	1	1	1	1320934-6	SUPPORT, TERMINAL	34
—	2	2	2	2	2	2	1-18024-0	SCR,BHC(M4X20)STRIP GUIDE	33
—	1	1	1	1	1	1	18027-2	WASHER, FLAT(M4)	32
—	1	1	1	1	1	1	1-18023-2	SCR,SKT CAP(M4X12)MOUNT BLOCK	31
—	1	1	1	1	1	1	1320908-8	SPACER, STRIP GUIDE	30
—	1	1	1	1	1	1	1633073-1	STRIP GUIDE PLATE ASSY	29
—	1	1	1	1	1	1	455888-9	SPACER, FRONT SHEAR DEP	28
—	2	2	2	2	2	2	1-22284-0	SPRING, DRAG	27
—	1	1	1	1	1	1	356835-1	LEVER, DRAG RELEASE	26
—	1	1	1	1	1	1	240792-1	DRAG, TERMINAL	25
—	1	1	1	1	1	1	1320928-1	PLATE, STRIP GUIDE	24
—	1	1	1	1	1	1	980371-4	SCR,SHC SHLD	23
—	1	—	1	1	—	1	690472-2	STRIPPER	22
—	1	1	1	1	1	1	1-18023-1	SCR,SHC(M4X10)STRIPPER	21
—	4	4	4	4	4	4	18025-2	WASHER,LOCK(M4)STRIPPER	20
—	—	1	—	—	1	—	690472-1	STRIPPER	19
									18
—	1	—	—	1	—	—	1338684-1	HOLDER, SHEAR, FRONT (NO-CUT)	17
									16</


Exploded view diagram of a mechanical assembly. The diagram shows the following components and their assembly points:

- Top Section:** A vertical assembly of a cap (37), a gasket (39), and a base plate (44) secured by a bolt (45) and a nut (63).
- Central Section:** A main body (44) with a handle (1) and a lever (2). The handle is secured with a pin (3) and a clip (4). The lever is secured with a pin (28) and a clip (5). A bolt (41) is used to secure the lever assembly.
- Bottom Section:** A base plate (46) with a handle (19) and a lever (21). The handle is secured with a pin (20) and a clip (22). The lever is secured with a pin (20) and a clip (22).
- Left Section:** A handle (33) with a pin (24) and a clip (30). The handle is secured with a pin (29) and a clip (29). A bolt (31) and a nut (32) are used to secure the handle assembly.
- Right Section:** A handle (34) with a pin (9) and a clip (12). The handle is secured with a pin (10) and a clip (17). A bolt (11) is used to secure the handle assembly.
- Assembly Points:**
 - A:** Indicated by a dashed line and a triangle, showing the assembly of the handle (1) and the lever (2).
 - B:** Indicated by a dashed line and a triangle, showing the assembly of the main body (44) and the handle (1).
 - C:** Indicated by a dashed line and a triangle, showing the assembly of the base plate (46) and the handle (19).

Legend:

- 1 AND SPARE PARTS
- 2 AND SPARE PARTS
- 6 AND SPARE PARTS
- SPARE PARTS KIT

ON INSTALLATION, SET WIRE
DISC TO LARGEST WIRE SIZE
SETTING. USE OF SETTINGS
BELOW MIN REQUIRED CRIMP
HEIGHT SETTING WILL CAUSE
DAMAGE TO CRIMP TOOLING.



-77			-76			-72			-71			-6			-2			-1			PART NO			DESCRIPTION			ITEM NO											
																								PARTS LIST														
QTY REQD PER ASSY																																						
THIS DRAWING IS A CONTROLLED DOCUMENT.																		DIV M. CLIFFORD CHK -			04AUG03						Tyco Electronics Corporation Harrisburg, PA 17105-3608											
DIMENSIONS:			TOLERANCES UNLESS OTHERWISE SPECIFIED:															APPRO F. BACKHURST			04AUG03			NAME			FINE ADJ SIDE FID HD-I APPL											
INCHES																		PRODUCT SPEC									-											
			0 PLC ±																								-											
			1 PLC ±																								-											
			2 PLC ± 0.5 [0.2 IN]																								-											
			3 PLC ±																								-											
MATERIAL			4 PLC ±																								-											
			FINISH																								-											
																		WEIGHT			-			SIZE CASE CODE DRAWING NO			RESTRICTED TO											
																					A1 00779 C=1528228			-														
CUSTOMER DRAWING																		SCALE			-			SHEET			1 OF 1			REV								