

## PCB terminal block - PT 1,5/ 4-PVH-5,0-A BKBDWH:-E3 - 1711201

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 4, pitch: 5 mm, connection method: Screw connection with wire protector, color: black, contact surface: Tin



The figure shows a 10-position version of the product

### Your advantages

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ High terminal block capacity thanks to rectangular terminal block space
- ✓ Allows connection of two conductors
- ✓ Horizontal and vertical connection option for optimum conductor routing
- ✓ Items that can be aligned in various pitches support flexible and space-saving PCB assembly



### Key Commercial Data

|              |                                                                                      |
|--------------|--------------------------------------------------------------------------------------|
| Packing unit | 250 pc                                                                               |
| GTIN         |  |
| GTIN         | 4055626233697                                                                        |

### Technical data

#### Dimensions

|              |         |
|--------------|---------|
| Length [ l ] | 14.9 mm |
| Height [ h ] | 11.3 mm |
| Pitch        | 5 mm    |
| Dimension a  | 5 mm    |

#### General

|                           |                                      |
|---------------------------|--------------------------------------|
| Range of articles         | PT 1,5/...-PVH-A                     |
| Number of positions       | 4                                    |
| Connection method         | Screw connection with wire protector |
| Insulating material group | I                                    |

## PCB terminal block - PT 1,5/ 4-PVH-5,0-A BKBDWH:-E3 - 1711201

### Technical data

#### General

|                                        |                     |
|----------------------------------------|---------------------|
| Rated voltage (III/2)                  | 320 V               |
| Nominal current $I_N$                  | 12 A                |
| Nominal cross section                  | 1.5 mm <sup>2</sup> |
| Flammability rating according to UL 94 | V0                  |
| Screw thread                           | M2,6                |

#### Standards and Regulations

|                                        |    |
|----------------------------------------|----|
| Flammability rating according to UL 94 | V0 |
|----------------------------------------|----|

#### Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| REACH SVHC | Lead 7439-92-1                                                                                      |
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

---

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>