



**TECHNICAL:**  
**LISTED:**  
 RATED SUPPLY VOLTAGE: 120 VAC  
 RATED CURRENT: UP TO 15 AMPS OR CABLE RATING  
 RESET TYPE: AUTOMATIC OR MANUAL  
 OPERATING FREQUENCY: 60 Hz  
 TYPE: CLASS A  
 GROUND TRIP CURRENT: 4-6 mA  
 OVERLOAD CURRENT: 90 AMP 125 VAC  
 INSULATION VOLTAGE: 1,500 VRMS – 1 MINUTE  
 ENDURANCE OPERATIONS: 3000 OPERATIONS

UL AND cUL  
 120 VAC  
 UP TO 15 AMPS OR CABLE RATING  
 AUTOMATIC OR MANUAL  
 60 Hz  
 CLASS A  
 4-6 mA  
 90 AMP 125 VAC  
 1,500 VRMS – 1 MINUTE  
 3000 OPERATIONS

INITIAL RELEASE EC NO.: IPG2013-1078	DRWN: HRUIZ01 2013/02/07	QUALITY SYMBOL ▽=0 ▽C=0
	CH'KD: HKNEELAN 2014/07/22	
	APPR: JFMURPHY 2015/04/20	
	REV A	

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	POWER-UP
1301530091	15054-1A	2 FT ± 1 IN	AUTO
1301530095	15054-25A	25 FT ± 2 IN	AUTO
1301530092	15054-1A	2 FT ± 1 IN	MANUAL
1301530096	15054-25M	25 FT ± 2 IN	MANUAL

GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION	
	mm	INCH	DRAWN BY DATE	TITLE			
4 PLACES	±---	±---	HRUIZ01 2013/02/07	120V 15A GFCI PLUG W/ MOLDED CONECTOR NEMA 5-15			
3 PLACES	±---	±.005	CHECKED BY DATE				
2 PLACES	±0.13	±.010	HKNEELAN 2014/07/22	MOLEX INCORPORATED			
1 PLACE	±0.25	±.020	APPROVED BY DATE				
ANGULAR ±1/2°		JFMURPHY 2015/04/20		DOCUMENT NO.		SHEET NO.	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE TABLE		SD-130153-017		1 OF 1	
SIZE C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					