

CDM7-600LR

**SURFACE MOUNT SILICON  
N-CHANNEL  
LR POWER MOSFET  
7.0 AMP, 600 VOLT**



www.centrasemi.com

**ULTRAMOS™**



**DPAK CASE**

**DESCRIPTION:**

The CENTRAL SEMICONDUCTOR CDM7-600LR is a 600 Volt N-Channel MOSFET designed for high voltage, fast switching applications such as Power Factor Correction (PFC), lighting and power inverters. This UltraMOS™ MOSFET combines high voltage capability with ultra low  $r_{DS(ON)}$ , low threshold voltage, and low gate charge for optimal efficiency.

**MARKING: FULL PART NUMBER**

**APPLICATIONS:**

- Power Factor Correction
- Alternative energy inverters
- Solid State Lighting (SSL)

**FEATURES:**

- High voltage capability ( $V_{DS}=600V$ )
- Low gate charge ( $Q_{gS}=2.62nC$  TYP)
- Ultra low  $r_{DS(ON)}$  ( $0.53\Omega$  TYP)

**MAXIMUM RATINGS:** ( $T_C=25^\circ C$  unless otherwise noted)

	<b>SYMBOL</b>		<b>UNITS</b>
Drain-Source Voltage	$V_{DS}$	600	V
Gate-Source Voltage	$V_{GS}$	30	V
Continuous Drain Current (Steady State)	$I_D$	7.0	A
Maximum Pulsed Drain Current, $t_p=10\mu s$	$I_{DM}$	28	A
Continuous Source Current (Body Diode)	$I_S$	7.0	A
Maximum Pulsed Source Current (Body Diode)	$I_{SM}$	28	A
Single Pulse Avalanche Energy (Note 1)	$E_{AS}$	145	mJ
Power Dissipation	$P_D$	60	W
Operating and Storage Junction Temperature	$T_J, T_{stg}$	-55 to +150	$^\circ C$
Thermal Resistance	$\theta_{JC}$	2.08	$^\circ C/W$
Thermal Resistance	$\theta_{JA}$	110	$^\circ C/W$

Note 1:  $L=30mH, I_{AS}=3.0A, V_{DD}=100V, R_G=25\Omega, \text{Initial } T_J=25^\circ C$

**ELECTRICAL CHARACTERISTICS:** ( $T_C=25^\circ C$  unless otherwise noted)

<b>SYMBOL</b>	<b>TEST CONDITIONS</b>	<b>MIN</b>	<b>TYP</b>	<b>MAX</b>	<b>UNITS</b>
$I_{GSSF}, I_{GSSR}$	$V_{GS}=30V, V_{DS}=0$			100	nA
$I_{DSS}$	$V_{DS}=600V, V_{GS}=0$		0.065	1.0	$\mu A$
$BV_{DSS}$	$V_{GS}=0, I_D=250\mu A$	600			V
$V_{GS(th)}$	$V_{GS}=V_{DS}, I_D=250\mu A$	2.0	3.0	4.0	V
$V_{SD}$	$V_{GS}=0, I_S=7.0A$		0.89	1.4	V
$r_{DS(ON)}$	$V_{GS}=10V, I_D=3.5A$		0.53	0.58	$\Omega$
$C_{rss}$	$V_{DS}=100V, V_{GS}=0, f=1.0MHz$		1.94		pF
$C_{iss}$	$V_{DS}=100V, V_{GS}=0, f=1.0MHz$		440		pF
$C_{oss}$	$V_{DS}=100V, V_{GS}=0, f=1.0MHz$		33		pF

R2 (10-August 2015)

**CDM7-600LR**

**SURFACE MOUNT SILICON  
N-CHANNEL  
LR POWER MOSFET  
7.0 AMP, 600 VOLT**




**ELECTRICAL CHARACTERISTICS - Continued:** ( $T_C=25^\circ\text{C}$  unless otherwise noted)

SYMBOL	TEST CONDITIONS	TYP	UNITS
$Q_{g(\text{tot})}$	$V_{DS}=480\text{V}, V_{GS}=10\text{V}, I_D=7.0\text{A}$ (Note 2)	14.5	nC
$Q_{gs}$	$V_{DS}=480\text{V}, V_{GS}=10\text{V}, I_D=7.0\text{A}$ (Note 2)	2.62	nC
$Q_{gd}$	$V_{DS}=480\text{V}, V_{GS}=10\text{V}, I_D=7.0\text{A}$ (Note 2)	7.4	nC
$t_{d(\text{on})}$	$V_{DD}=300\text{V}, V_{GS}=10\text{V}, I_D=7.0\text{A}, R_G=24\Omega$ (Note 2)	9.4	ns
$t_r$	$V_{DD}=300\text{V}, V_{GS}=10\text{V}, I_D=7.0\text{A}, R_G=24\Omega$ (Note 2)	26	ns
$t_{d(\text{off})}$	$V_{DD}=300\text{V}, V_{GS}=10\text{V}, I_D=7.0\text{A}, R_G=24\Omega$ (Note 2)	44	ns
$t_f$	$V_{DD}=300\text{V}, V_{GS}=10\text{V}, I_D=7.0\text{A}, R_G=24\Omega$ (Note 2)	26	ns
$t_{rr}$	$V_{GS}=0, I_S=7.0\text{A}, di/dt=100\text{A}/\mu\text{s}$ (Note 2)	283	ns
$Q_{rr}$	$V_{GS}=0, I_S=7.0\text{A}, di/dt=100\text{A}/\mu\text{s}$ (Note 2)	2.73	$\mu\text{C}$

Note 2: Pulse Width  $\leq 300\mu\text{s}$ , Duty Cycle  $\leq 2\%$


**DPAK CASE - MECHANICAL OUTLINE**



SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.083	0.108	2.10	2.75
B	0.016	0.032	0.40	0.81
C	0.035	0.063	0.89	1.60
D	0.203	0.228	5.15	5.79
E	0.020	-	0.51	-
F	0.018	0.024	0.45	0.60
G	0.051	0.071	1.30	1.80
H	0.248	0.268	6.30	6.81
J	0.197	0.217	5.00	5.50
K	0.209	0.245	5.30	6.22
L	0.025	0.040	0.64	1.02
M	0.090	0.115	2.30	2.91
N	0.012	0.045	0.30	1.14
P	0.180		4.60	
R	0.090		2.30	

DPAK (REV: R0)

**PIN CONFIGURATION**



**LEAD CODE:**

- 1) Gate
  - 2) Drain
  - 3) Source
  - 4) Drain
- Pin 2 is common to the tab (4)

**MARKING: FULL PART NUMBER**






R2 (10-August 2015)

CDM7-600LR

SURFACE MOUNT SILICON  
N-CHANNEL  
LR POWER MOSFET  
7.0 AMP, 600 VOLT



TYPICAL ELECTRICAL CHARACTERISTICS



R2 (10-August 2015)

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)