


FLORENTINA-1-O


~45° + 15° oval beam

TECHNICAL SPECIFICATIONS:

Dimensions	39.7 mm
Height	13 mm
Fastening	tape
ROHS compliant	yes 


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
ROSE-CMC-O	Single lens	PC	clear	
FLORENTINA-1-HLD	Holder	PC	black	
ROSE-TAPE	Tape	PU tape	black	



ORDERING INFORMATION:



Component		Qty in box	MOQ	MPQ	Box weight (kg)
FCA15452_FLORENTINA-1-O	Single lens	840		60	7.9
» Box size: 480 x 280 x 300 mm					





PHOTOMETRIC DATA (MEASURED):





LED Bridgelux SMD 5050
 FWHM 42.0 + 24.0°
 Efficiency 71 %
 Peak intensity 2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C15427_FLORENTINA-1-SHD-60





LED XHP35 HD
 FWHM 42.0 + 21.0°
 Efficiency 71 %
 Peak intensity 2.3 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C15427_FLORENTINA-1-SHD-60



LED XHP35 HI
 FWHM 28.0°
 Efficiency 72 %
 Peak intensity 2.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:





LED XP-G2
 FWHM 44.0 + 18.0°
 Efficiency 73 %
 Peak intensity 2.8 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:
 C15427_FLORENTINA-1-SHD-60





PHOTOMETRIC DATA (MEASURED):





LED XP-L HD
FWHM 43.0 + 19.0°
Efficiency 71 %
Peak intensity 2.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60





LED XP-L2
FWHM 43.0 + 20.0°
Efficiency 69 %
Peak intensity 2.3 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60



LED XT-E
FWHM 44.0 + 16.0°
Efficiency 71 %
Peak intensity 2.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60





LED LG 5630
FWHM 45.0 + 17.0°
Efficiency 77 %
Peak intensity 2.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C16701_FLORENTINA-1-SHD-60-WHT





PHOTOMETRIC DATA (MEASURED):





LED LG 5630
FWHM 45.0 + 16.0°
Efficiency 75 %
Peak intensity 2.9 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60





LED LUXEON 3030 2D (Round LES)
FWHM 45.0 + 14.0°
Efficiency 75 %
Peak intensity 3.4 cd/Im
LEDs/each optic 1
Light colour White
Required components:



LED LUXEON 5050 Round LES
FWHM 42.0 + 22.0°
Efficiency 72 %
Peak intensity 2.2 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60





LED LUXEON TX
FWHM 44.0 + 17.0°
Efficiency 72 %
Peak intensity 2.8 cd/Im
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60





PHOTOMETRIC DATA (MEASURED):





LED NF2x757G
FWHM 45.0 + 15.0°
Efficiency 75 %
Peak intensity 3.2 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C16701_FLORENTINA-1-SHD-60-WHT





LED NF2x757G
FWHM 44.0 + 15.0°
Efficiency 76 %
Peak intensity 3.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60



LED NVSW319B
FWHM 43.0 + 20.0°
Efficiency 74 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60



LED NVSxx19B/NVSxx19C
FWHM 44.0 + 17.0°
Efficiency 72 %
Peak intensity 2.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60




PHOTOMETRIC DATA (MEASURED):

OSRAM

Opto Semiconductors



LED OSLON Square CSSRM2/CSSRM3
FWHM 44.0 + 17.0°
Efficiency 74 %
Peak intensity 2.9 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60



OSRAM



Opto Semiconductors

LED OSLON SSL 150
FWHM 45.0 + 15.0°
Efficiency 72 %
Peak intensity 3.3 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60




SAMSUNG

LED LM561B
FWHM 45.0 + 15.0°
Efficiency 75 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60



SEOUL SEMICONDUCTOR



LED SEOUL 5630
FWHM 45.0 + 15.0°
Efficiency 77 %
Peak intensity 3.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60



PHOTOMETRIC DATA (MEASURED):




LED Z8Y22P
FWHM 44.0 + 17.0°
Efficiency 69 %
Peak intensity 2.7 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60



PHOTOMETRIC DATA (SIMULATED):



LED XP-G2 HE
FWHM 42.0 + 22.0°
Efficiency 82 %
Peak intensity 2.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:
C15427_FLORENTINA-1-SHD-60



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)