



DIMENSIONS




TERMINATION



ORDERING INFORMATION



SERIES	8609	3	48	7	3	13	7	4	5	ELF
ROWS FITTED WITH CONTACTS										
ROW a	-	-	-	-	-	-	-	-	-	16
ROW a b c	-	-	-	-	-	-	-	-	-	48
ROW a - c	-	-	-	-	-	-	-	-	-	32
NO. OF CONTACTS										
TYPE OF INSULATOR										
3 ROW MALE INSULATOR										7
METHOD OF MOUNTING										
STANDARD MOUNTING - STYLE C/2										3
TERMINATION										
ANGLED SPILL										13
OPTIONS										
NO OPTION										7
WITH HARPOONS										H
PERFORMANCE CLASS										
DIN 41612 CLASS 3										4
DIN 41612 CLASS 2										5
DIN 41612 CLASS 1										6
AS PER MIL C 55302 / JSS 50808										8
PITCH PER ROW										
2.54 mm										5
LEAD FREE VERSION										ELF

PCB LAYOUT



GENERAL CHARACTERISTICS & RoHS INFO

REFER DRAWING C-8609-0000A

mat'l. code SEE DWG C-8609-0000A				surface ISO 1302 ✓		tolerance ISO 406 ISO 1101		projection 		product family 8609			
ltr		ecn no		dr		date		tolerances unless otherwise specified		title			
A		104-0063		MINI		2004-09-17		angles linear	0.X ±0.1			DIN STANDARD HEADER DIN 41612 STYLE C/2	
B		104-0100		MINI		2004-11-09			0.XX ±0.1				
C		105-0089		MINI		2005-05-19			0.XXX ±0.1				
D		106-0061		MINI		2006-05-31		dr		MINI K V		2004-09-17	
E		108-0146		KR		2008-10-21		enr		RAKHEE G		2004-09-17	
F		109-0217		KR		2009-10-13		chr		KESAVAN R		2010-01-13	
G		110-0020		KR		2010-01-13		appd		KESAVAN R		2010-01-13	
sheet index		revision		G									
		sheet		1									