

Cable gland - G-INSEC-PG36-L68N-NNES-S - 1411202

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 22 mm ... 32 mm, Shielding: Yes, Connecting thread: Pg36, Color: silver

Product Features



Key commercial data

Packing unit	1 pc
Minimum order quantity	5 pc
Custom tariff number	74199990
Country of origin	Turkey

Technical data

Dimensions

Length	57 mm
Length without connecting thread	48 mm
Connecting thread diameter	47 mm
Wrench size, union nut	50 mm
Wrench size, support	50 mm
Hexagon angular dimension GRP	55.5 mm
Length of the connecting thread	9 mm
External cable diameter	22 mm ... 32 mm

Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-40 °C ... 100 °C

Cable gland - G-INSEC-PG36-L68N-NNES-S - 1411202

Technical data

General

Cable gland material	Brass, nickel-plated
Seal material	CR
Cable seal material	CR
O-ring material	NBR
Shielded	Yes
Thread type on connection side	Pg36
Torque	35 Nm ... 45 Nm (Union nut)
Color	silver

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals


Approvals

UL Recognized

Ex Approvals

Approvals submitted

Approval details

UL Recognized 

Cable gland - G-INSEC-PG36-L68N-NNES-S - 1411202

Drawings

Dimensional drawing

