

UK Power (Mains) Plug, Cord Connector (Rewireable), 3 pole, Angled



Description

- 1 Function:
- attachment plug,
- Cable diameter max. 11.0 mm
- Clip for Pins

References

Last order date: 31.12.2013


Weblinks

[pdf-datasheet](#), [html-datasheet](#), [General Product Information](#), [Approvals](#), [CE declaration of conformity](#), [RoHS](#), [CHINA-RoHS](#), [REACH](#), [Mating Connectors](#), [e-Shop](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#), [CAD-Drawings](#), [Accessories](#), [Detailed request for product](#)

Technical Data

Ratings IEC	13A / 250VAC; 50Hz
Ratings UL/CSA	13A / 250VAC; 60Hz
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 40 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class I acc. to IEC 61140
Material: Housing	white

Dimensions



Config. Code

1363 - H - A B C 0 - D - E J

The characters are placeholders for the correspondingly keys of selections from the key tables.

1363 - **H** - A B C 0 - D - E J = Type

Type

Configuration
key

resale product

A

1363 - H - A B C 0 - D - E J = Terminals

Terminal L	Configuration key
screw terminal	A

1363 - H - A B C 0 - D - E J = Terminals

Terminal N	Configuration key
screw terminal	A
Symbols similar as in table A	

1363 - H - A B C 0 - D - E J = Terminals

Terminal Ground	Configuration key
screw terminal	A
Symbols similar as in table A	

1363 - H - A B C 0 - D - E J = Color

Color	Configuration key
White	D

1363 - H - A B C 0 - D - E J = Style

Style	Configuration key
for cord assembly	8

1363 - H - A B C 0 - D - E J = Condition

Condition	Configuration key
assembled	1

All Variants

Config. Code	Description	Order Number
1363--0--	1363, Power Plug (Mains Socket), , 70°C, version: I, L : , N: , ground: , color: , design:	4311.0070

The listet variants should be available from stock Other versions on request www.schurter.com/contact

Packaging unit	10 Pcs
----------------	--------

PHASE